

**G Series****Sunlite 25 Watt Silver Bowl G16.5 Globe,  
Candelabra Base,**

G16.5 Globe

**DESCRIPTION:**

Sunlite, 25 watt incandescent candelabra based G16.5 globe silverbowl bulb works with most 120 volt lighting fixtures, will provide 150 lumens of light output, and will last for an average of 0.9 years. This silverbowl light bulbs are used as a directional light source. The lamps can be used in settings such as restaurants, prayer houses, warehouses, as well as residential areas. The silverbowl lamp creates a warm welcoming setting when entering a room. silverbowl lamps are a wonderful way to direct light to reduce glare and eliminate direct light. The attractive silverbowl Finish reflects the light upward into the fixture to create a more pleasing and romantic atmosphere. Incandescent lighting is commonly used for decorative, office, residential, commercial and special purpose lamps. These bulbs are also great for decorative and special purpose lighting applications.

**FEATURES:**

- 25-Watt. 120-Volt
- N/A Lumens
- 1500 Hours Average Lamp Life
- Candelabra Base
- 25G16.5/SB



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	G16.5
<b>Average Rated Hours</b>	1500
<b>Finish</b>	Clear
<b>Base</b>	Candelabra Screw (E12)
<b>Average Life Span Years</b>	1

### Electrical Characteristics

<b>Watts</b>	25
<b>Volts</b>	120

### Light Characteristics

<b>Coating</b>	Silver Bowl
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	2600K

### Additional Features

<b>Title 20</b>	Lawful for sale in California
<b>Mercury Free</b>	Yes

### Product Dimensions

<b>MOL (in)</b>	2.85
<b>Diameter (in)</b>	1.95"
<b>Item Dimension (in)</b>	(W) 1.95 (H) 2.77 (D) 1.95
<b>Package Dimension (in)</b>	(W) 2 (H) 2.4 (D) 2.1
<b>Package Weight (lb)</b>	0.050

### Product Data

<b>Case Unit Rate</b>	25
<b>Pack Size</b>	1
<b>Item UPC</b>	653703012032



**VARIATIONS:**



01203-SU



01248-SU

<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
01203-SU	25G16.5	25	2600K WW	1500	1
01248-SU	40G16.5	40	2600K WW	1500	1