

Sunlite 49099-SU LED 12" Modern Square Flush Mount Ceiling Light Fixture, 20 Watt, (100 Watt Equivalent), 1000 Lumens, Dimmable, Brushed Nickel Finish, ETL Listed For Damp Location 27K - Warm White

## **DESCRIPTION:**

Contemporary design meets modern technology in the LED Flush Mount Half Band and Half Glass fixtures from Sunlite. The decorative brushed nickel base houses a frosted glass lens for even light distribution. This dimmable fixture uses only 20 watts of electricity while putting out 1000 lumens of light (equal to a 100 watt fixture). Integrated LEDs means there are no bulbs to replace. And with a 50,000 hour life span you'll enjoy years of reliable and maintenance-free service. ETL Listed for damp location installation. IP20 Rated. Hardware and installation instructions included. Fixture dimensions are 11 inches x 11 inches x 3 inches. Tested LED Compatible dimmers: LEVITON- 6631-L, 6633-PL, 6674, IP106, IPL06. LUTRON- CT-600P, CTCL-153P, CTCL-153PDH, DV-600P, DVCL-153P, MACL-153MR, MACL-153P, S-600P, S-603PR, SCL-153PR. TGCL-153PH.

### **FEATURES:**

- LED TECHNOLOGY Integrated dimmable LEDs use only 20 watts of electricity while putting out 1000 lumens of light (equal to a 100 watt fixture). Maintenance free with no bulbs to replace. Warm white light output at 2700K.
- CONTEMPORARY DESIGN The decorative brushed nickel base houses a frosted glass lens for even light distribution. The modern half glass and contemporary half band fixture will add a beautiful touch to any room. Fixture dimensions are 11 inches x 11 inches x 3 inches.
- DIMMABLE Light is dimmable when attached to an LED compatible dimmer switch. Tested LED Compatible dimmers: LEVITON- 6631-L, 6633-PL, 6674, IPI06, IPL06. LUTRON- CT-600P, CTCL-153P, CTCL-153PDH, DV-600P, DVCL-153P, MACL-153MR, MACL-153P, S-600P, S-603PR, SCL-153PR, TGCL-153PH.
- 50,000 HOUR LIFE SPAN With a 50,000 hour life span you'll enjoy years of reliable and maintenance-free service.
- ETL LISTED This fixture is ETL Listed for damp location installation. IP20 Rated. Hardware and installation instructions included.



## SPECIFICATIONS:

#### **General Characteristics**

Integrated LED

**Brushed Nickel** 

Incandescent)

Steel & Glass

10-100%

Glass

Glass

Frosted

2700K 120°

Integrated

Forward Phase (Triac or

50000

46

Yes

**Bulb Shape** Average Rated Hours

**Finish** 

Average Life Span Years

Dimmable

**Dimming Type** 

**Dimming Percentage** 

Material Lens Louver Lens Material

Lens Finish **Bulb Type** 

## **Electrical Characteristics**

Watts 20 120 Volts Equivalent Wattage 120 0.97 Power Factor **Temperature** 0° to 40° C

# **Light Characteristics**

Lumens Brightness 1000 Color Rendering Index CRI 81 Soft White

**Emitted Color** 

Color Temperature Kelvin

Beam Angle

#### Fixture Characteristics

Shape Square Number of Lights 1 Surface Mounting LED Fixture Technology Use Location Indoor

## Additional Features

Safety Rating Mark ETL - Damp Location Safety Rated For Canada Yes

Safety Rated For USA Yes

## **Product Dimensions**

Size Item Dimension (in) Item Weight (Ib) Package Dimension (in) Package Weight (lb)

# **Product Data**

Case Unit Rate Item UPC Warranty Years 12"

(W) 11 (H) 3 (D) 11

4.200

(W) 13.2 (H) 5.5 (D) 13.2

5.300

6

653703490991

5



# **ACCESSORIES:**

Catalog # 98952-CMP Universal