

## Sunlite 49167-SU LED Slim Profile Outdoor Wall Pack Fixture, 50K - Super White, 8625 Lumen, 75 Watt, Bronze Finish

### DESCRIPTION:

Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. These wall mount fixtures provide a bright 8625 lumen output at 5000K Super White color temperature. An adjustable base allows you to direct the light for optimal coverage. With 96 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours. Each fixture uses 75 watts of electricity and has an estimated yearly energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) The weather-resistant aluminum body is finished in bronze. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 120-277 volt electrical service. ETL Listed for wet location installation and DLC Listed for quality and efficiency.

### FEATURES:

- **LED TECHNOLOGY** - Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. An adjustable base allows you to direct the light for optimal coverage. With 96 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours.
- **ENERGY EFFICIENT** - Using 75 watts of energy these fixtures have a low estimated yearly energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) These fixtures will provide significant savings in electricity over their lifetime with no bulbs to replace.
- **MAXIMUM LIGHT OUTPUT** - Each fixture gives off a bright 8625 lumen with 5000K super white color temperature.
- **MULTIPLE OUTDOOR USES** - These commercial grade fixtures feature a weather-resistant aluminum body finished in bronze. Ideal for security and general purpose lighting along the perimeter of buildings, entryways, or anywhere extra lighting is needed.
- **ETL AND DLC LISTED** - These fixtures are ETL Listed for wet location installation and DLC Listed for quality and efficiency. They operate on 120-277 volt electrical service.

## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	Integrated LED
<b>Average Rated Hours</b>	50000
<b>Finish</b>	Bronze
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	No
<b>Material</b>	Metal
<b>Lens Finish</b>	Clear
<b>Bulb Type</b>	Integrated

### Electrical Characteristics

<b>Watts</b>	75
<b>Volts</b>	120-277
<b>Equivalent Wattage</b>	250-400
<b>LED Chip Manufacturer</b>	Philips 3030
<b>Power Factor</b>	0.92
<b>Temperature</b>	-40° to 40° C

### Light Characteristics

<b>Lumens Brightness</b>	8625
<b>Color Rendering Index CRI</b>	70
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K
<b>Beam Angle</b>	100°-80°
<b>Mercury Content</b>	5

### Fixture Characteristics

<b>Number of Lights</b>	1
<b>Mounting</b>	Wall
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Outdoor

### Additional Features

<b>Safety Rating Mark</b>	ETL Listed - Wet Location
<b>Safety Rated For Canada</b>	Yes
<b>Safety Rated For USA</b>	Yes
<b>DLC</b>	Yes
<b>DLC Number</b>	PRVLA70X
<b>DLC Classification</b>	Standard

### Product Dimensions

<b>Item Dimension (in)</b>	(W) 9.64 (H) 10.43 (D) 4.25
<b>Package Dimension (in)</b>	(W) 12.99 (H) 4.8 (D) 13.62
<b>Package Weight (lb)</b>	8.100

### Product Data

<b>Case Unit Rate</b>	6
<b>Item UPC</b>	653703491677
<b>Warranty Years</b>	5