

Sunlite 49168-SU LED Slim Profile Outdoor Wall Pack Fixture, 50K - Super White, 8625 Lumen, 75 Watt, White Finish

DESCRIPTION:

Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. These wall mount fixtures provide a bright 8625 lumen output at 5000K Super White color temperature. An adjustable base allows you to direct the light for optimal coverage. With 96 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours. Each fixture uses 75 watts of electricity and has an estimated yearly energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) The weather-resistant aluminum body is finished in white. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 120-277 volt electrical service. ETL Listed for wet location installation and DLC Listed for quality and efficiency.

FEATURES:

- **LED TECHNOLOGY** - Sunlite LED Slim Profile Downlight fixtures are designed to provide ample outdoor illumination. An adjustable base allows you to direct the light for optimal coverage. With 96 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours.
- **ENERGY EFFICIENT** - Using 75 watts of energy these fixtures have a low estimated yearly energy cost of \$9.03. (Based on 3 hours/day use at \$0.11/kWh) These fixtures will provide significant savings in electricity over their lifetime with no bulbs to replace.
- **MAXIMUM LIGHT OUTPUT** - Each fixture gives off a bright 8625 lumen with 5000K super white color temperature.
- **MULTIPLE OUTDOOR USES** - These commercial grade fixtures feature a weather-resistant aluminum body finished in white. Ideal for security and general purpose lighting along the perimeter of buildings, entryways, or anywhere extra lighting is needed.
- **ETL AND DLC LISTED** - These fixtures are ETL Listed for wet location installation and DLC Listed for quality and efficiency. They operate on 120-277 volt electrical service.

SPECIFICATIONS:

General Characteristics

Bulb Shape	Integrated LED
Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	No
Material	Metal
Lens Finish	Clear
Bulb Type	Integrated

Electrical Characteristics

Watts	75
Volts	120-277
Equivalent Wattage	250-400
LED Chip Manufacturer	Philips 3030
Power Factor	0.92
Temperature	-40° to 40° C

Light Characteristics

Lumens Brightness	8625
Color Rendering Index CRI	70
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	100°-80°
Mercury Content	5

Fixture Characteristics

Number of Lights	1
Mounting	Wall
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PRVLA70X
DLC Classification	Standard

Product Dimensions

Item Dimension (in)	(W) 9.64 (H) 10.43 (D) 4.25
Item Weight (lb)	6.550
Package Dimension (in)	(W) 12.99 (H) 4.8 (D) 13.62
Package Weight (lb)	8.100

Product Data

Case Unit Rate	6
Item UPC	653703491684
Warranty Years	5