

Sunlite 49173 LED Outdoor Slim Profile Cutoff Wallpack Light Fixture, Power Selectable 30/40/50W, 6500 Lmns, Color Selectable 30/40/50K, Dimmable, UL Listed, Bronze, Residential, Commercial Use

DESCRIPTION:

Upgrade your outdoor lighting with the Sunlite LED Outdoor Slim Profile Wallpack. This fixture is a simple, economical solution for your outdoor lighting needs. It provides high-quality illumination in a compact unit that is perfect for commercial and multi-residential lighting applications. Hinged base allows you to adjust the light up to 90 degrees so you can direct the light where it's needed. These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 30 watts, 40 watts, or 50 watts. The lighting output can be dimmed when connected to an LED-compatible dimmer switch (0-10V) allowing you to adjust the brightness to suit your needs and provide up to 6500 high output lumens depending on the watts you've chosen. These commercial grade fixtures feature a weather-resistant aluminum body finished in bronze. Ideal for security and general-purpose lighting along the perimeter of buildings, entryways, or anywhere extra lighting is needed. It is protected from low pressure water jets coming from any direction, condensation, and water spray thanks to its IP 65 rating. UL Listed for safety and quality. DLC listed for design and efficiency. Great for commercial or residential applications on 120–277-volt service. Dimension: 10.89" H x 8.50" W x 4.86" D.

FEATURES:

- **SLIM PROFILE DESIGN** – This fixture is a simple, economical solution for your outdoor lighting needs. It provides high-quality illumination in a compact unit that is perfect for commercial and multi-residential lighting applications. Hinged base allows you to adjust the light up to 90 degrees so you can direct the light where it's needed.
- **COLOR & POWER SELECTABLE** - These fixtures allow you to choose the color temperature at the time of installation. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 30 watts, 40 watts, or 50 watts.
- **DIMMABLE** - The lighting output can be dimmed when connected to an LED-compatible dimmer switch (0-10V) allowing you to adjust the brightness to suit your needs and provide up to 6500 high output lumens depending on the watts you've chosen.

SPECIFICATIONS:

General Characteristics

| | |
|--------------------------------|-------------------|
| Average Rated Hours | 50000 |
| Finish | Dark Bronze |
| Average Life Span Years | 46 |
| Dimmable | Yes |
| Dimming Type | 0-10V Low Voltage |
| Dimming Percentage | 0-100% |
| Material | Aluminum |
| Lens Material | Polycarbonate |
| Lens Finish | Clear |

Electrical Characteristics

| | |
|------------------------------|-------------|
| Watts | 30/40/50W |
| Volts | 120-347 |
| LED Chip Manufacturer | 2835 |
| Power Factor | 0.9 |
| Temperature | -40°F-113°F |

Light Characteristics

| | |
|----------------------------------|----------------|
| Lumens Brightness | 3900/5200/6500 |
| Color Rendering Index CRI | 80 |
| Emitted Color | CCT Selectable |
| Color Temperature Kelvin | 30K/40K/50K |
| Beam Angle | 92° |
| Flicker | Yes |

Fixture Characteristics

| | |
|---------------------------|---------|
| Mounting | Wall |
| Fixture Technology | LED |
| Use Location | Outdoor |

Additional Features

| | |
|--------------------------------|--------------------------|
| Safety Rating Mark | UL Listed - Wet Location |
| Safety Rated For Canada | Yes |
| Safety Rated For USA | Yes |
| Mercury Free | Yes |

Product Dimensions

| | |
|-------------------------------|-----------------------------|
| Item Dimension (in) | (W) 8.5 (H) 10.9 (D) 4.85 |
| Package Dimension (in) | (W) 9.88 (H) 12.25 (D) 5.75 |
| Package Weight (lb) | 5.46 |

Product Data

| | |
|-----------------------|--------------|
| Case Unit Rate | 4 |
| Item UPC | 653703491738 |
| Warranty Years | 5 |