### Bi-Pin

## Sunlite FCS 150W/T4/24V/CL/G6.35 150-watt 24-volt Bi-Pin Based Stage and Studio T4 Bulb, Clear

### DESCRIPTION:

*Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.*

### FEATURES:

- 
- 
- 
- 
-

# sunlite®

## SPECIFICATIONS:

### General Characteristics

| | |
|---|---|
| *Bulb Shape* | *T4* |
| *Ansi code* | *FCs* |
| *Average Rated Hours* | *50* |
| *Finish* | *Clear* |
| *Average Life Span Years* | *0* |

### Electrical Characteristics

| | |
|---|---|
| *Amps* | *6.25* |
| *Watts* | *150* |
| *Volts* | *24* |
| *Filament* | *C-6F* |

### Light Characteristics

| | |
|---|---|
| *Lumens Brightness* | *6000* |
| *Color Rendering Index CRI* | *99* |
| *Color Temperature Kelvin* | *3400K* |

### Product Dimensions

| | |
|---|---|
| *Item Dimension (in)* | *(W) 0.45 (H) 1.79 (D) 0* |
| *Package Dimension (in)* | *(W) 2.7 (H) 0.8 (D) 0.9* |
| *Package Weight (lb)* | *0.05* |

### Product Data

| | |
|---|---|
| *Case Unit Rate* | *10* |
| *Pack Size* | *1* |
| *Item UPC* | *653703702100* |