

Sunlite 55415-SU GFCI Duplex Outlet, 20 Amp, 120 VAC, 2 Pole/3 Wire, Tamper Resistant, Wallplate Included, ETL Listed, White 1 Pack

GFCI

DESCRIPTION:

Sunlite tamper resistant GFCI decorative duplex receptacles feature integrated shutters to keep kids and pets safe. These grounded outlets are simple to install and include a matching color wallplate. GFCI outlets protect from dangerous electrical shocks resulting from faulty appliances or in wet locations like kitchens, bathrooms, and utility rooms as required by electrical code. Flush, deco-style design gives an updated look for new construction, renovation projects, and replacement in commercial and residential installations. Built-in test and reset buttons with LED indicator light. For 20 Amp, 120 VAC Service. 2 pole / 3 wire. ETL Listed.

FEATURES:

- **GFCI OUTLET** - Ground Fault Circuit Interrupter (GFCI) outlets protect from dangerous electrical shocks resulting from faulty appliances or in wet locations like kitchens, bathrooms, and utility rooms as required by electrical code.
- **SAFETY FIRST** - 3-prong grounded outlets feature integrated tamper resistant shutters to keep kids and pets safe. Self-test GFCI helps ensure continuous protection. Built-in test and reset buttons with LED indicator light. ETL Listed.
- **DECO STYLE** - Flush, deco-style duplex design gives an updated look and includes a matching color wallplate.
- **MULTIPLE USES** - Gives an updated look for new construction, renovation projects, and replacement in commercial and residential applications.
- **EASY INSTALLATION** - Simple installation in fewer than 15 minutes using only a screw driver. Can be wired to protect all standard outlets on the same circuit. For 20 Amp, 120 VAC service. 2 pole / 3 wire.



SPECIFICATIONS:

Electrical Characteristics

Amps | 20

Additional Features

Safety Rating Mark | ETL Listed

Product Dimensions

Package Dimension (in) | (W) 3.1 (H) 1.7 (D) 5.1

Package Weight (lb) | 0.3500

Product Data

Case Unit Rate | 12

Pack Size | 1

Item UPC | 653703554150

