

Catalog # 80527-SU PAR16/LED/7W/GU10/40K

Par Series

Sunlite 80527 LED MR16 Reflector Spotlight Bulb, 7 Watts (50W Halogen Bulb Replacement) 120 Volt, 550 Lumen, 35° Flood Beam, GU10 Base, Dimmable, ETL Listed, 4000K Cool White, 1 Count

High Efficiency

DESCRIPTION:

Sunlite MR16 LED 120 volt reflector bulbs are dimmable and have been designed to give you up to 25,000 hours of reliable service. That means fewer replacements for difficult to reach bulbs. These durable led bulbs provide the same output as a 50-watt bulb while only using 7 watts of energy. With upgrading to LED technology, you will get a bulb that is cooler to the touch and instant-on at full brightness with no warmup time. This bulb is ETL Listed and features a GU10 Base.

FEATURES:

- UPGRADE TO LED Upgrade your old 120V halogen bulbs with energy efficient LED technology. With a light output of 550 lumens our MR16 LED bulbs use only 7 watts of electricity but are equal to a 50W halogen bulb
- Dimmable Emits a dimmable Cool White light at 4000K. Ideal for recessed lighting, track lighting, and other fixtures with a GU10 base. High color rendering index rating of 80 for more vivid and true colors. 35-degree beam angle
- LONG LIFE Made of shatter-proof plastic these bulbs are cooler than traditional incandescent and halogen bulbs when lit. With an average lifespan of 25,000 hours our LED MR16's will reduce cost and the hassle of replacing hard to reach bulbs
- ENERGY STAR CERTIFIED The annual operating cost is a low \$0.84 per bulb (Based on 3 hours/day at \$0.11 per/kWh). That is an 84% electricity savings over incandescent bulbs. Installing these bulbs may qualify you for state and local energy rebates
- ETL LISTED These LED bulbs are ETL Listed and are tested to meet their rigorous safety standards. Unlike incandescent bulbs, they contain no harmful chemicals and do not require special handling or disposal



sunlite

SPECIFICATIONS:

General Characteristics

Average Rated Hours

Average Life Span Years

Bulb Shape

Dimmable

Material

Base

Pro	duct	Dime	nsions

	MOL (in)	1.97
	Diameter (in)	2.11
ock (GU10)	Item Dimension (in)	(W) 1.97 (H) 2.48 (D) 1.97
. ,	Package Dimension (in)	(W) 2 (H) 2.25 (D) 2
	Package Weight (lb)	0.09
n & Plastic		

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703805276
Warranty Years	3
Package Type	Box

Electrical	Characteristics
Watte	

Watts	7
Volts	120
Equivalent Wattage	50
LED Chip Manufacturer	SMD2835
Power Factor	0.8
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	550
Color Rendering Index CRI	80
R9 Rating	12
CBCP	595
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Beam Angle	35°
Beam Angle Description	Flood

Additional Features

Safety Rating Mark	ETL - Damp Location	
Energy Star	Yes	
Energy Star Number	2388807	



744 Clinton Street Brooklyn, NY, 11231 | 718.768.7000

PAR16 25000 Twist & Lo Yes Aluminum & Plastic

23