

### Corn Series

## Sunlite LED Corn Bulb 54W (85 -125W Equivalent) Light Bulb Medium (E26) Base, Corn Cob

### DESCRIPTION:

Sunlite Lighting's LED corn cob bulb lamps deliver a potent and flicker-free ray of light to any setting. Utilizing only 54-watts of energy to produce a stunning 1700K - 1900K amber light in addition to offering significant energy savings when compared to competing lamps. Ideal for various indoor and outdoor settings while not utilizing any hazardous chemicals, such as mercury. With an average lamp life of 40000 hours, Sunlite Lighting's corn cob lamps are your go to for any wide area lighting needs. Important note: ballast or bypass ballast must be removed to allow corn cob lamp to function. Works only with a/c current.

### FEATURES:

- This 360° beam spread corn cob lamp produces an efficient 1700K - 1900K amber beam of light at a powerful 4320 lumens while utilizing 100 - 277 volts
- On average, this LED corn cob lamp lasts an astonishing 40000 hours and features 180 energy saving diodes
- Ideal for all post lights, Street lights, security Lighting, high bay lights while also designed for indoor as well as outdoor usage
- Significantly lower electricity usage and cost by replacing a 85w-125w high pressure sodium mh metal halide light with Sunlite LED corn cob lamp that only consume 54W
- High-quality, Damp location ready, UL listed, modern replacement LED corn cob lamp sold at a highly competitive price

## SPECIFICATIONS:

### General Characteristics

|                                |                    |
|--------------------------------|--------------------|
| <b>Bulb Shape</b>              | Corn               |
| <b>Average Rated Hours</b>     | 40000              |
| <b>Finish</b>                  | Clear              |
| <b>Base</b>                    | Medium Screw (E26) |
| <b>Average Life Span Years</b> | 36                 |
| <b>Dimmable</b>                | No                 |
| <b>Material</b>                | Plastic            |

### Electrical Characteristics

|                              |              |
|------------------------------|--------------|
| <b>Watts</b>                 | 54           |
| <b>Volts</b>                 | 100-277      |
| <b>Equivalent Wattage</b>    | 100          |
| <b>LED Chip Manufacturer</b> | Epistar 5730 |
| <b>Power Factor</b>          | 0.9          |
| <b>Temperature</b>           | -30° to 55°  |

### Light Characteristics

|                                 |             |
|---------------------------------|-------------|
| <b>Lumens Brightness</b>        | 4320        |
| <b>Emitted Color</b>            | Amber       |
| <b>Color Temperature Kelvin</b> | 1700K-1900K |
| <b>Beam Angle</b>               | 360°        |

### Additional Features

|                                   |                           |
|-----------------------------------|---------------------------|
| <b>Safety Rating Mark</b>         | UL Listed - Damp Location |
| <b>UL Rated Enclosed Fixtures</b> | Yes                       |
| <b>Safety Rated For Canada</b>    | Yes                       |
| <b>Safety Rated For USA</b>       | Yes                       |

### Product Dimensions

|                               |                             |
|-------------------------------|-----------------------------|
| <b>MOL (in)</b>               | 10.94                       |
| <b>Diameter (in)</b>          | 3.54                        |
| <b>Item Dimension (in)</b>    | (W) 3.54 (H) 10.94 (D) 3.54 |
| <b>Package Dimension (in)</b> | (W) 4.25 (H) 12.51 (D) 4.25 |
| <b>Package Weight (lb)</b>    | 2.730                       |

### Product Data

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 12           |
| <b>Pack Size</b>      | 1            |
| <b>Item UPC</b>       | 653703805825 |
| <b>Warranty Years</b> | 5            |
| <b>Package Type</b>   | Box          |