

T Series

Sunlite 80873 LED Metal Halide, HPS, HID High Bay Replacement Light Bulb, 140 Watts (400W Equivalent) 20000 Lumen, Mogul (E39) Base, 120-277 Volts, Non Dimmable, UL Listed, 5000K Daylight, 1 Pack

High Lumen Lamps

DESCRIPTION:

Sunlite LED High Bay bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warmup time. Each bulb gives off a bright 20000 lumen at 5000K Daylight color temperature. Provides as much light as a 400 watt bulb while only using 140 watts of electricity. With a 50,000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications. UL Listed for Damp Location Installation. They have a mogul (E39) base and a wide flood 120 degree beam spread.

FEATURES:

- **UPGRADE TO LED** - Our Sunlite LED High Bay bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. They are instant on at full brightness with no warmup time
- **At 20000 lumens** this high bay replacement led gives out as much light as a 400 watt bulb while only using 140 watts of electricity! Estimated yearly energy cost is a low \$16.86. (Based on 3 hours/day use at \$0.11/kWh)
- **LONG LIFE** - With a 50000 hour lifespan these led light bulbs Replace Metal Halide, HPS and HID lamps and will provide significant savings in electricity over their lifetime it will also require you to replace hard to reach bulbs less often
- **UL LISTED** - These bulbs are UL Listed for Damp Location installations. Our high bay retrofits are multi-volt they can use 120-277 volts of electricity and have a mogul (E39) base
- **BALLAST BYPASS REQUIRED** - These LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions can be found online or consult an electrician for more information



SPECIFICATIONS:

General Characteristics

Bulb Shape	Other
Average Rated Hours	50000
Finish	White
Base	Mogul Screw (E39)
Average Life Span Years	46
Dimmable	No
Material	Aluminum & Plastic

Electrical Characteristics

Watts	140
Volts	120-277
Equivalent Wattage	400
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20-50

Light Characteristics

Lumens Brightness	20000
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	120°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
---------------------------	---------------------------

Product Dimensions

MOL (in)	12.13
Diameter (in)	9.05
Item Dimension (in)	(W) 12.13 (H) 9.05 (D) 9.05
Package Dimension (in)	(W) 13 (H) 9.6 (D) 9.6
Package Weight (lb)	3.26

Product Data

Case Unit Rate	4
Pack Size	1
Item UPC	653703808734
Warranty Years	5
Package Type	Box