

**G Series**

**Sunlite 05358-SU Sunlite CFL G30 Globe Light Bulb, 20 Watts (75W Equivalent), 120 Volts, Medium (E26) Base, Compact Fluorescent, 900 Lumen Output, 8,000 Life Hours, UL Listed, 50K - Super White Globe**

**DESCRIPTION:**

*Sunlite Compact Fluorescent G30 Globe Bulbs deliver energy efficient, super white light. Consuming only 20 watts of energy while putting out as much light at a 75 watt, they offer significant energy savings over incandescent bulbs. 5000K super white color temperature and 900 lumen output. Ideal for kitchens, study areas, security lighting, or anywhere bright task lighting is needed. These glass globe bulbs remain cooler to the touch when lit. They are medium based bulbs (E26) and fit in most fixtures. With a lamp life of 8,000 hours they last more than 6 times longer than incandescent bulbs. UL Listed. Bulbs are 3.72 inches in diameter and 5.86 inches in overall height.*

**FEATURES:**

- **COMPACT FLUORESCENT** - Sunlite CFL Globe Bulbs are an energy efficient, long life solution to your lighting needs.
- **ENERGY EFFICIENT** - Using only 20 watts these compact fluorescent bulbs put out as much light as 75 watt incandescent bulbs.
- **SUPER WHITE** - Super white color temperature (5000K) provides ample task lighting for kitchens, study areas, workshops, or anywhere you need bright light. 900 Lumen output.
- **LONG LIFE** - These cool to the touch bulbs have an average life of up to 8,000 hours they last more than 6 times longer than incandescent bulbs.
- **UL LISTED** - Tested to meet UL's strict design and safety requirements. Bulbs are 3.72 inches in diameter and 5.86 inches in overall height.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	G30
<b>Average Rated Hours</b>	8000
<b>Base</b>	Medium Screw (E26)
<b>Average Life Span Years</b>	7

### Electrical Characteristics

<b>Watts</b>	20
<b>Volts</b>	120

### Light Characteristics

<b>Lumens Brightness</b>	900
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K

### Additional Features

<b>Safety Rating Mark</b>	UL Listed
<b>FCT Label Mercury Content</b>	Yes

### Product Dimensions

<b>MOL (in)</b>	5.86
<b>Diameter (in)</b>	3.715"
<b>Item Dimension (in)</b>	(W) 3.71 (H) 5.86 (D) 3.71
<b>Package Dimension (in)</b>	(W) 4 (H) 6.25 (D) 4
<b>Package Weight (lb)</b>	0.480

### Product Data

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	1
<b>Item UPC</b>	653703053585
<b>Package Type</b>	Box



**VARIATIONS:**



05358-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
05358-SU	SLG20/G30	20	900	80	5000K SW	8000	1