

**ST Series** 

# Sunlite F21T5/830 21-Watt T5 Linear Fluorescent Light Bulb Mini Bi Pin Base, 3000K, 40-Pack

T5 High Performance Straight Tube

# **DESCRIPTION:**

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Perfomance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30315-SU F21T5/830 3000K Color Temperature T5 Hight Performance Straight Tube Fluorescent 21 Watt lamp features a Mini Bi Pin base, provides a light output of 1900 lumens at a Color Rendering Index (CRI) of 82 and can last an average of 20000 hours.



- The package length is 87.375 centimeters
- The package height is 11.176 centimeters
- The package width is 16.51 centimeters
- Package Weight: 8.25 pounds





# **SPECIFICATIONS:**

### **General Characteristics**

Bulb Shape Average Rated Hours Base

Average Life Span Years

**Electrical Characteristics** 

Watts

**Light Characteristics** 

Lumens Brightness
Color Rendering Index CRI
Emitted Color

Color Temperature Kelvin

**Additional Features** 

**Rohs Compliant** 

T5 20000

Miniature Bi-Pin (G5)

18

21

1900 82

Warm White

3000K

Yes

# **Product Dimensions**

Size
MOL (in)
Diameter (in)
Item Dimension (in)
Package Dimension (in)
Package Weight (lb)

3 Foot 34.00 0.625" (W) 0.63 (H) 0.63 (D) 34 (W) 0.64 (H) 0.64 (D) 34

#### **Product Data**

Case Unit Rate Pack Size Item UPC

1 653703303154

0.23

40

