

FLUSH MOUNT FIXTURE INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

Turn off the main power at the circuit breaker before installing the fixture, in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

ASSEMBLY & INSTALLATION

1. Pull the **supply wires** (5, 6, & 7) out from the **outlet box** (1). Attach the **mounting bracket** (2) to the **outlet box** (1) using the slotted holes on the **mounting bracket** (2) and the **mounting screws** (3) provided.

2. Thread the **fixture screws** (4) two full turns into the appropriate threaded holes in the **mounting bracket** (2). (Check the **mounting bracket** (2) against the fixture **key hole slots** (13) to ensure proper fit.)

3. Connect the **black supply wire** (6) to the **black fixture wire** (9) and **white supply wire** (5) to the **white fixture wire** (8) using **wire connectors** (11). Connect the **fixture ground wire** (10) to the **supply ground wire** (7) using a **wire connector** (11).

4. Carefully tuck all wiring back into the **outlet box** (1). Locate the **fixture pan** (12) over the **outlet box** (1), positioning the **fixture screws** (4) heads through the large openings of the **key hole slots** (13). Rotate the **fixture pan** (12) to seat the screws, and tighten securely. (FIG. 2)

5. Set **Glass Shade** (14) into **Cage** (15). Position **Cage** (15) over **Fixture Pan** (12) and secure with two **Cage Mounting Screw** (16). (FIG. 1)

INSTALLATION IS NOW COMPLETE.

