

G Series

Filament

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

- •
- •
- •
- •





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours **Finish** Base

Average Life Span Years Dimmable

Dimming Type

Material

Electrical Characteristics

Watts 8.5 Volts 120 100 Equivalent Wattage Power Factor 0.7 -4°F - 104°F **Temperature**

Filament

Light Characteristics

800 Lumens Brightness Color Rendering Index CRI 90

Emitted Color Amber Light Color Temperature Kelvin 2200K 360° Beam Angle

Beam Angle Description Omni-Directional

Flicker

Additional Features

Safety Rating Mark **UL Rated Enclosed Fixtures** Mercury Free

UL Listed - Wet Location

Yes Yes

No

G25

15000

Clear

14

Yes

Glass

4

Medium Screw (E26)

Forward Phase (Triac or

Incandescent)

Product Dimensions

MOL (in) 4.65 Item Dimension (in) (W) 3.1 (H) 4.6 (D) 3.1 Item Weight (Ib) 0.18 Package Dimension (in) (W) 3.38 (H) 5.38 (D) 3.38 Package Weight (lb) 0.18

Product Data

Case Unit Rate Pack Size Item UPC Warranty Years Package Type

6

653703812298

2 Вох