

G Series

Sunlite 81254 LED G30 Virtual Filament Globe Light Bulb, 3.5 Watts (15W Equivalent), 120 Lumens, Medium E26 Base, Clear Glass, Dimmable, Acrylic Inner Pillar, UL Listed, 2000K Amber, 1 Pack

Filament

DESCRIPTION:

Sunlite LED amber globe bulbs are designed to give you up to 15,000 hours of reliable service. That means fewer replacements for difficult to reach bulbs. These unique bulbs feature removable glass globe and virtual filament design. Output is a amber glow at 2000K. They are dimmable and energy efficient using only 3.5 watts of electricity. The annual operating cost is only \$0.42 (Based on 3 hours/day at \$0.11/kWh). And LED technology means they are cool to the touch when lit and instant-on at full brightness. The standard medium base (E26) make them the perfect bulb for wall sconces, decorative lamps, pendants, and many other fixtures. UL Listed for damp location installation. Ideal for both residential and commercial use.



- UPGRADE TO LED Easily upgrade your decorative lighting with energy efficient 3.5 Watts (15W Equivalent), LED technology. These medium based (E26) bulbs are the perfect decorative bulb
- VIRTUAL FILAMENT STYLE These amber glass G30 globes feature a removable cover and virtual filament for a unique look. The etched zigzag pattern glows when lit creating an interesting effect. They are the perfect bulb for wall sconces, decorative lamps, pendants, and many other fixtures
- LONG LIFE BULBS With LED technology you save cost and the hassle of replacing hard to reach bulbs. They have an average life of 15,000 hours. The annual energy cost is a low \$0.42 per bulb (based on 3 hours/day at \$0.11 per/kWh)
- DIMMABLE Emits a dimmable amber glow at 2000K.
 Cozy 120 lumen output ideal for decorative applications
- UL LISTED They are UL Listed for damp location installation. And LED technology means they are cool to the touch when lit and instant-on at full brightness. For residential and commercial applications







SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Base

Average Life Span Years Ingress Protection

Dimmable Material

Electrical Characteristics

 Watts
 3.5

 Volts
 120

 Power Factor
 0.7

 Temperature
 -20?-40?

Light Characteristics

Lumens Brightness120Color Rendering Index CRI80Emitted ColorWarm WhiteColor Temperature Kelvin2000KBeam Angle300°

Additional Features

Safety Rating Mark UL Listed - Damp Location

G30

15000

Amber

14

Yes

Glass

Medium Screw (E26)

IP20 (12.5 mm solids, Not

protected from liquids)

Product Dimensions

 MOL (in)
 5.55

 Diameter (in)
 3.73

 Item Dimension (in)
 (W) 3.74 (H) 5.49 (D) 3.74

 Item Weight (Ib)
 0.300

 Package Dimension (in)
 (W) 4 (H) 6.05 (D) 4

 Package Weight (Ib)
 0.35

Product Data

 Case Unit Rate
 6

 Pack Size
 1

 Item UPC
 653703812540

 Warranty Years
 2

 Package Type
 Box



