

Catalog # 81262-SU HL/LED/T36/E26/27W/50K

T Series

Sunlite 81262-SU LED T36 Super Bright High Lumen Corn Light Bulb, 27 Watts (300W Equivalent) 3500 Lumens, Medium e26 Base, 120-277 Multi Volt, Non-Dimmable, 50K-Super White, UL Listed-Wet Location

High Lumen Lamps

DESCRIPTION:

Sunlite Bullet LED T36 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time. Each bulb contains 106 LEDs giving off a bright 3500 lumen at 5000K Super White color temperature. Provides as much light as a 300 watt bulb while only using 27 watts of electricity. With a 50000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications. UL Listed for Damp Location Installation. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). The 220 degree beam angle gives a broader spread than UFO bulbs and more downlight than corn bulbs.

FEATURES:

- UPGRADE TO LED These LED T36 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time.
- ENERGY EFFICIENT These bulbs give out as much light as a 300 incandescent watt bulb while only using 27 watts of electricity. Estimated yearly energy cost is a low \$3.25. (Based on 3 hours/day use at \$0.11/kWh)
- HIGH LUMEN OUTPUT LED Bullet Bulbs provide 220 degree lighting coverage giving them a broader spread than UFO bulbs and more downlight than corn bulbs. Each bulb contains 106 LEDs and gives off a bright 3500 lumen output with Warm White 3000K color temperature.
- LONG LIFE With a 50,000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications.
- UL LISTED These bulbs are UL Listed for Wet Location installations. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). For use in 120-277 volt fixtures. Ingress protection (IP) rating of 44.



sunlite

SPECIFICATIONS:

General Characteristics

Bulb Shape	T36	MOL (in)	7.09
Average Rated Hours	50000	Diameter (in)	3.94
Finish	White	Package Dimension (in)	(W) 7.5 (H) 4.3 (D) 4.2
Base	Medium Screw (E26)	Package Weight (lb)	1.4
Average Life Span Years	46		
Dimmable	No	Product Data	
Material	PC Cover & Aluminum	Case Unit Rate	6
		Pack Size	1

Electrical Characteristics

Watts	27
Volts	120-277
Equivalent Wattage	300
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20-45?

MOL (in)	7.09
Diameter (in)	3.94
Package Dimension (in)	(W) 7.5 (H) 4.3 (D) 4.2
Package Weight (lb)	1.4

Case Unit Rate
Pack Size
Item UPC
Warranty Years
Package Type

653703812625 3 Box

Light Characteristics

Lumens Brightness	3500
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	220°
Flicker	<30%

Additional Features

Safety Rating Mark

UL Listed - Wet Location