

**R Series****Sunlite 82035-SU LED 90 CRI R20 Reflector Bulb, 7 Watts (50W Equivalent), 525 Lumens, Dimmable, Medium Base (E26), Wide 105° Beam Angle, ETL Listed, 30K - Warm White 6 Pack**

90CRI Series

**DESCRIPTION:**

Sunlite 24-Inch Linear Battery Backup LED Fixtures are an energy efficient lighting option for ceiling or wall mounting. Built-in battery will provide up to 90 minutes of light in the event of a power outage. These hard wired fixtures are simple to install on any junction box and include installation hardware. Durable steel and plastic construction. Output is a bright 3000 lumen while only using 25 watts of electricity. Low annual energy costs of \$3.01 (Based on 3 Hours/Day at \$0.11/kWh). With integrated LEDs and a long 50,000 hour life span these fixtures will provide years of reliable and maintenance-free service. And unlike fluorescent tubes they are instant on at full brightness and contain no harmful chemicals. UL Listed for damp location installation. DLC Listed for quality and design. These indoor fixtures are ideal for residential or commercial installations in stairwells, corridors, storage areas, basements, garages, or anywhere extra lighting is needed.

**FEATURES:**

- **UPGRADE TO LED** - Easily upgrade your old bulbs with energy efficient LED technology. These dimmable bulbs use only 7 watts of electricity but are equal to a 50 watt incandescent bulb. Yet unlike incandescent or halogen bulbs they remain cooler to the touch.
- **DIMMABLE** - Emits a dimmable and comfortable warm white light at 3000K. Ideal for recessed cans, track lighting and other indoor fixtures with a medium (E26) base. High Color Rendering Index (CRI) rating of 90 for more vivid and true colors. Wide 105° beam angle.
- **LONG LIFE BULBS** - With an average life of 25,000 hours these LED bulbs provide years of reliable service and save the cost and hassle of replacing hard to reach bulbs.
- **ENERGY STAR CERTIFIED** - Installing these Energy Star Certified bulbs may qualify you for state and local energy rebates. Provides 525 lumens of light instantly with no warm up time needed. Mercury-free so there is no harmful hazardous waste. Standard R20 form factor. Overall length is 3.93 inches, 2.48 inches in diameter.
- **ETL LISTED** - These bulbs are ETL Listed for safety and quality. Ideal for both residential and commercial applications.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	R20
<b>Average Rated Hours</b>	25000
<b>Base</b>	Medium Screw (E26)
<b>Average Life Span Years</b>	23
<b>Dimmable</b>	Yes
<b>Material</b>	Plastic

### Electrical Characteristics

<b>Watts</b>	7
<b>Volts</b>	120
<b>Equivalent Wattage</b>	50
<b>LED Chip Manufacturer</b>	Bridgelux
<b>Power Factor</b>	0.9
<b>Temperature</b>	-20-45?

### Light Characteristics

<b>Lumens Brightness</b>	525
<b>Color Rendering Index CRI</b>	90
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	3000K
<b>Beam Angle</b>	105°

### Additional Features

<b>Safety Rating Mark</b>	ETL - Damp Location
<b>Energy Star</b>	Yes
<b>Energy Star Number</b>	2347049

### Product Dimensions

<b>MOL (in)</b>	3.93
<b>Diameter (in)</b>	2.48
<b>Item Dimension (in)</b>	(W) 2.48 (H) 3.91 (D) 2.48
<b>Item Weight (lb)</b>	0.015
<b>Package Dimension (in)</b>	(W) 4.5 (H) 7.8 (D) 5.7
<b>Package Weight (lb)</b>	1.050

### Product Data

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	6
<b>Item UPC</b>	653703820354
<b>Warranty Years</b>	3
<b>Package Type</b>	Box

