

ST Series

Sunlite 87929 LED T8 Plug & Play light Tube (Type A) 4 foot, 15 Watt (32W Equivalent) 2100 Lumens, Medium G13 Bi-Pin Base, Dual End Connection, Electronic Ballast Compatible, 6500K Daylight, 25 Pack

Plug and Play

DESCRIPTION:

Upgrade your T8/T12 fluorescent bulbs with energy efficient LED plug and play bulbs, a direct replacement with no ballast bypass required. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you will be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time. Can be used for both commercial and residential locations. They are DLC & UL Listed and unlike fluorescent tubes, they contain no harmful chemicals and do not require special handling or disposal.

FEATURES:

- UPGRADE TO LED replace your inefficient T8/T12 fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Glass outer tubes prevent yellowing and bending over time. Our wide 170 beam angle with frosted shatter resistant glass gives you great light coverage. High Color Rendering Index (CRI) rating of 82
- PLUG AND PLAY These bulbs are direct replacements for T8/T12 medium 2-pin base (G13) fluorescent tubes with no bypass required. For use with electronic ballasts only. You can find a complete list of compatible ballasts included in the pdf in this listing
- ENERGY EFFICIENT Each bulb puts out a bright 2100 lumens of light with a 6500K Daylight color temperature while only using 15 watts of electricity. Annual energy costs are a low \$1.81 (Based on 3 hours/day at \$0.11/kWh)
- LONG LIFE With a life span of up to 50,000 hours you'll be required to replace difficult to access bulbs less often. You will save maintenance costs and save energy at the same time
- DLC AND UL LISTED These LED bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also DLC listed for quality and efficiency. And unlike fluorescent tubes, they contain no harmful chemicals and do not require special handling or disposal





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Base

Average Life Span Years Dimmable

Material

Electrical Characteristics

Watts 15
Volts 120-277
Equivalent Wattage 32
LED Chip Manufacturer 2835
Power Factor 0.9
Temperature 45?

Light Characteristics

Lumens Brightness2200Color Rendering Index CRI82CBCP300°Emitted ColorDaylightColor Temperature Kelvin6500KBeam Angle170°

Additional Features

Safety Rating Mark
UL Rated Enclosed Fixtures
DLC Classification

UL Listed - Damp Location

Yes Standard

T8

46

Yes

50000

White

Medium 2-Pin (G13)

Glass & plastic

Product Dimensions

 MOL (in)
 47.7

 Diameter (in)
 1.02

 Package Dimension (in)
 (W) 1.2 (H) 1.2 (D) 48

 Package Weight (lb)
 0.200

Product Data

Package Type

 Case Unit Rate
 25

 Pack Size
 1

 Item UPC
 653703879291

 Warranty Years
 5

Sleeve