

Sunlite 82092-SU LED 24-Inch Linear Light Fixture, Built-in Battery Backup, 25 Watts, 3000 Lumen, 120-277 Volt, Dimmable, Indoor, Wall or Ceiling Mount, White Finish, UL Listed, 40K - Cool White 2 Feet

DESCRIPTION:

Sunlite 48-Inch Linear Battery Backup LED Fixtures are an energy efficient lighting option for ceiling or wall mounting. Built-in battery will provide up to 90 minutes of light in the event of a power outage. These hard wired fixtures are simple to install on any junction box and include installation hardware. Durable steel and plastic construction. Output is a bright 4800 lumen while only using 40 watts of electricity. Low annual energy costs of \$4.82 (Based on 3 Hours/Day at \$0.11/kWh). With integrated LEDs and a long 50,000 hour life span these fixtures will provide years of reliable and maintenance-free service. And unlike fluorescent tubes they are instant on at full brightness and contain no harmful chemicals. UL Listed for damp location installation. DLC Listed for quality and design. These indoor fixtures are ideal for residential or commercial installations in stairwells, corridors, storage areas, basements, garages, or anywhere extra lighting is needed.

FEATURES:

- LED TECHNOLOGY These 24-Inch fixtures have built-in LEDs that never need replacing. Color temperature is 4000K (cool white). These long life fixtures are ideal commercial or residential installations.
- BUILT-IN BATTERY BACKUP In the event of a power outage this fixture will provide up to 90 minutes of light using the integrated battery. Battery charges/recharges automatically while power is on.
- LONG LIFE With integrated LEDs and a long 50,000 hour life span these fixtures will provide years of reliable and maintenance-free service.
- ENERGY EFFICIENT Each fixture puts out 3000 lumens of light and only uses 25 watts of electricity. Estimated annual energy cost is a low \$3.01 (Based on 3 hours/day at \$0.11/kWh).
- UL LISTED These fixtures are UL Listed for safety and quality and DLC Listed for efficient design. Installation is simple on any junction box. Installation hardware is included. They can be ceiling or wall mounted and feature durable steel construction. And unlike fluorescent tube fixtures they contain no harmful chemicals. Fixture dimensions (W) 3.60 in (H) 4.30 in (L) 24.40 in.



SPECIFICATIONS:

General Characteristics

Average Rated Hours

Finish

Average Life Span Years

Dimmable

Dimming Type

Bulb Shape

Dimming Percentage

Material

Lens Description Lens Material Lens Finish **Bulb Type**

Integrated LED

50000 White 46

Yes

0-10V Low Voltage

10-100% Steel Prismatic Plastic White Integrated **Product Dimensions**

Size

Item Dimension (in) Package Dimension (in)

Package Weight (lb)

Product Data

Case Unit Rate

Item UPC

Warranty Years

24"

(W) 3.6 (H) 4.3 (D) 24.4 (W) 26 (H) 5.2 (D) 4

6.000

653703820927

5

6

Electrical Characteristics

Watts 25 Volts 120-277 Power Factor 0.95

Light Characteristics

3000 Lumens Brightness Color Rendering Index CRI 80

Cool White **Emitted Color** 4000K Color Temperature Kelvin

Fixture Characteristics

Traditional Style Shape Square **Number of Lights** 1 Wall Mounting LED Fixture Technology Use Location Indoor

Additional Features

Safety Rating Mark UL Listed - Damp Location

Safety Rated For Canada Yes Safety Rated For USA Yes DLC Yes

DLC Number PLLR0ERPBXGR

DLC Classification Standard