

Sunlite 82096 2-Foot LED Linear Strip Light, Wraparound Fixture, Adjustable 3 CCT 3000K-5000K, 18 Watts, 2340 LMN, Dimmable, 50,000 Hour Life Span, 80 CRI, Surface Mount, Steel Body, UL & DLC Listed

Wraparound

DESCRIPTION:

Sunlite LED 2-Foot Linear Strip Light Fixtures are an energy-efficient and maintenance-free lighting solution. These hardwired fixtures have built-in LEDs, so there are no bulbs to replace. When connected to an LED-compatible dimmer, you can adjust the light output to suit your needs. These multi-volt 120-277V fixtures are ideal for commercial, industrial, and residential applicationsâ€"steel bodies with an acrylic lens designed for indoor use. With a 50,000-hour life span, these fixtures will provide years of maintenance-free service. Each fixture uses only 18 Watts of electricity and has an adjustable color temperature. They are ETL listed for damp location use and DLC listed for efficiency and design. The lens is made of shatterproof acrylic, and unlike fluorescent tube fixtures, they contain no harmful chemicals.

FEATURES:

- LED TECHNOLOGY The Sunlite Strip Light Fixture is an excellent addition to any atmosphere. It features a slim, robust steel frame and a shatter-resistant frosted lens. LED wraparound lights are the ideal method for replacing traditional fluorescent lamps. These 2-Foot-long lamps have built-in LEDs, so there are no bulbs to replace, making these a maintenance-free solution. Also, their service life is five times that of the standard fluorescent strip lights.
- DIMMABLE The fixture can be dimmed when installed with an LED-compatible dimmer. Output is a bright 2340 lumens while only using 18 watts of electricity. Operates within 120-277V AC, 10%-100% dimming range, low voltage dimmers capability (0-10V), and has a high color rendering at 80 CRI. The long 50,000-hour life span is significant in energy savings over time.
- ADJUSTABLE COLOR TEMPERATURE: Test different color temperatures before installation and never be dissatisfied with CCT again. This simplistic fixture has adjustable LED color-changing technology (3000K, 4000K, 5000K), quickly meeting different demands in areas. With a simple switch inside the fixture, the color temperature is adjusted to your desire. PLEASE NOTE: select the desired color temperature before completely mounting the fixture. (Instructions included)
- EASY INSTALLATION- The LED strip light is easily installed on any junction box and can be mounted in two ways, surface and suspension. Directly mount this LED Wraparound fixture to the ceiling for bright light in offices, garages, basements, warehouses, and storage areas.



SPECIFICATIONS:

General Characteristics

Average Rated Hours 5000
Finish White
Average Life Span Years 46

Dimmable Y
Dimming Type 0

Dimming Percentage

Material
Lens Description
Lens Material
Lens Finish

50000 White 46 Yes

0-10V Low Voltage

0-100% Steel Prismatic Acrylic White

Product Dimensions

 Size
 24"

 Item Dimension (in)
 (W) 4.13 (H) 3.77 (D) 23.93

 Package Dimension (in)
 (W) 4.52 (H) 4.33 (D) 24.6

 Package Weight (Ib)
 3.01

Product Data

Case Unit Rate Item UPC Warranty Years 4 653703820965 5

Electrical Characteristics

 Watts
 18

 Volts
 120-277

 LED Chip Manufacturer
 SMD2835

 Power Factor
 0.9

 Temperature
 -4°F - 104°F

Light Characteristics

Lumens Brightness2340Color Rendering Index CRI80

Emitted ColorCCT SelectableColor Temperature Kelvin30K/40K/50KBeam Angle101

Fixture Characteristics

ShapeRectangleMountingWallFixture TechnologyLEDUse LocationIndoor

Additional Features

Safety Rating Mark ETL - Damp Location

DLC Yes

DLC Number PL7NABMAJVER

DLC Classification Standard



ACCESSORIES:

Catalog # 05806-SU RPG/LFX/BB213/2FT