

#### A Series

Sunlite 82108 LED A23 Light Bulb, 26 Watts (300w Equivalent), High Output, 4000 Lumens, Medium E26 Base, 120-227 Multi-Volt, Non-Dimmable, UL Listed, 3000K Warm White

Household

#### **DESCRIPTION:**

Upgrade the lighting in your home or business with Sunlite energy saving LED bulbs. With a larger A23 shape and medium (E26) base they are an energy efficient replacement for 300 HID High-intensity discharge lamps while only using 26 watts of electricity. And unlike HID lamps, they are instant-on at full 4000 lumen brightness. With an average life of 25,000 hours these bulbs the estimated annual energy cost is a low \$3.13 (Based on 3 hr. /day use at \$0. 11 per/kWh). Perfect for any fixtures, including wall sconces, ceiling lights, vanity lights, closet fixtures, table lamps, garage door openers, porch, patio and pole lights. These bulbs are UL Listed for Damp Location installation. Save more energy in an efficient way with this LED high voltage bulb. 120-277V, High voltage bulbs use less energy and thus keeps your electricity bills low, making this a perfect option for commercial and industrial use.

#### FEATURES:

- UPGRADE TO LED These multi-volt 26 Watt A23 LED bulbs are an energy efficient replacement to High-intensity discharge lamps (HID). They have a medium (E26) base and remain cool to the touch even when lit. And unlike HID bulbs, they are instant-on at full 4000 lumen brightness
- WARM WHITE At 3000K these warm white bulbs provide a comforting glow in bedrooms, living spaces or anywhere you want to set relaxed mood. 80 CRI.
- SAVE ENERGY Get the same light output of a 300 watt incandescent bulb while saving on electricity. The annual energy cost is a low \$3.13 (Based on 3 hours/day at \$0. 11 per/kWh) With an average life span of 25,000 hours
- MULTI-VOLT Save energy in an efficient way with this LED bulb high voltage bulb. Multi volt 120-277V. High voltage bulbs use less energy and thus keeps your electricity bills low, making this a perfect option for commercial and industrial use.
- THE SAFER CHOICE These bulbs are UL Listed for Damp Location installation. Ideal for both residential and commercial use. These bulbs contain no mercury or other harmful chemicals.



# sunlite

## **SPECIFICATIONS:**

#### **General Characteristics**

| Prod | luct | Dim | ensi | ons |
|------|------|-----|------|-----|
|      |      |     |      |     |

| Bulb Shape              | A23                | MOL (in)               | 6.5                        |
|-------------------------|--------------------|------------------------|----------------------------|
| Average Rated Hours     | 25000              | Diameter (in)          | 3.15                       |
| Finish                  | White              | Package Dimension (in) | (W) 3.25 (H) 6.75 (D) 3.25 |
| Base                    | Medium Screw (E26) | Package Weight (lb)    | 1.07                       |
| Average Life Span Years | 23                 |                        |                            |
| Dimmable                | No                 | Product Data           |                            |
| Material                | PC & Aluminum      | Case Unit Rate         | 6                          |
|                         |                    | Pack Size              | 1                          |

#### **Electrical Characteristics**

| Watts                 | 26      |
|-----------------------|---------|
| Volts                 | 120-277 |
| Equivalent Wattage    | 300     |
| LED Chip Manufacturer | 2835    |
| Power Factor          | 0.9     |
| Temperature           | -20-45? |

| 6.5                        |
|----------------------------|
| 3.15                       |
| (W) 3.25 (H) 6.75 (D) 3.25 |
| 1.07                       |
|                            |

| Case Unit Rate |
|----------------|
| Pack Size      |
| Item UPC       |
| Warranty Years |
| Package Type   |

653703821085 3 Box

#### **Light Characteristics**

| Lumens Brightness         | 4000       |
|---------------------------|------------|
| Color Rendering Index CRI | 80         |
| Emitted Color             | Warm White |
| Color Temperature Kelvin  | 3000K      |
| Beam Angle                | 220°       |
| Flicker                   | <30%       |

### **Additional Features**

Safety Rating Mark

UL Listed - Damp Location