

## ST Series

**Sunlite 88164 4-Foot LED T8 Tubular  
Light Bulb, 15 Watts, 1800 Lumens,  
5000K Daylight, Medium G13 Bi-Pin Base,  
120-277V, Single-End Bypass, UL & DLC  
Listed, F28T5, F32T8, F40T12, 1 Pack**  
Bypass Single End**DESCRIPTION:**

*Sunlite's LED Filament T8 Tubular Light Bulb is a great way to add a touch of class to your home. Long life LED technology means up to 50,000 hours of reliable service while only using 15 watts of electricity with a lumen rating of 1800, so you'll need replace difficult to access bulbs less often. At 5000K these daylight bulbs provide a natural glow in bedrooms, living spaces or anywhere you want to set a bright lighting environment. These indoor bulbs are UL Listed for damp location installation. It also meets the necessary ratings for Canada and is rated for totally enclosed fixtures. Ideal for both residential and commercial use. Dimensions 47.67" Length x .98" Diameter.*

**FEATURES:**

- **UPGRADE TO LED** - Replace your inefficient bulbs with energy saving LED bulbs from Sunlite. Long life LED technology means up to 50,000 hours of reliable service while only using 15 watts of electricity with a lumen rating of 1800, so you'll need replace difficult to access bulbs less often.
- **SINGLE END BYPASS** – This bulb removes the need for a ballast that reduces energy consumption. It makes installation more manageable as you don't have to handle wiring at both ends.
- **G13 2-PIN BASE** - This provides a secure and stable connection between your fixture and the bulb, ensuring a consistent light flow without flickering or power loss.
- **DAYLIGHT** - At 5000K these daylight bulbs provide a natural glow in bedrooms, living spaces or anywhere you want to set a bright lighting environment.
- **THE SAFER CHOICE** – These indoor bulbs are UL Listed for damp location installation. It also meets the necessary ratings for Canada and is rated for totally enclosed fixtures. Ideal for both residential and commercial use. Dimensions 47.67" Length x .98" Diameter.

## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	T8
<b>Average Rated Hours</b>	50000
<b>Finish</b>	White
<b>Base</b>	Medium 2-Pin (G13)
<b>Average Life Span Years</b>	46
<b>Dimmable</b>	No
<b>Material</b>	Glass

### Electrical Characteristics

<b>Watts</b>	15
<b>Volts</b>	120-277
<b>Equivalent Wattage</b>	F28T5, F32T8, F40T12
<b>Power Factor</b>	0.9
<b>Temperature</b>	-20° to 45°

### Light Characteristics

<b>Lumens Brightness</b>	1800
<b>Color Rendering Index CRI</b>	82
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K
<b>Beam Angle</b>	220°

### Additional Features

<b>Safety Rating Mark</b>	UL Classified - Damp Location
<b>UL Rated Enclosed Fixtures</b>	Yes
<b>Safety Rated For Canada</b>	Yes
<b>Safety Rated For USA</b>	Yes
<b>DLC</b>	Yes
<b>DLC Number</b>	PLJXJVEIMO3U
<b>DLC Classification</b>	Standard

### Product Dimensions

<b>Size</b>	4 Foot
<b>MOL (in)</b>	47.67
<b>Diameter (in)</b>	0.98
<b>Item Dimension (in)</b>	(W) 0.98 (H) 0.98 (D) 47.67
<b>Item Weight (lb)</b>	0.760
<b>Package Dimension (in)</b>	(W) 1.1 (H) 47.62 (D) 1.1
<b>Package Weight (lb)</b>	0.520

### Product Data

<b>Case Unit Rate</b>	10
<b>Pack Size</b>	1
<b>Item UPC</b>	653703881645
<b>Warranty Years</b>	5
<b>Package Type</b>	Sleeve