

**Sunlite 85462-SU LED 2-Pack 1x4 Foot
Lay-in Light Panel Fixtures, Color
Selectable 35K/40K/50K, Power
Selectable 20W/30W/40W, 3600-4520
Lmns, 120/277 Volt, 0-10V Dimmable, UL
& DLC Listed, 1 by 4 FT**

DESCRIPTION:

Sunlite 2-Pack LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. These color and power selectable fixtures features innovative technology that allows you to choose the color temperature and light output at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 20 watts, 30 watts, or 40 watts. White finish and opaque diffuser for even light distribution. These fixtures have a built-in 120/277 volt dimmable driver for use with low voltage (0-10V) dimming controls. No maintenance, 50, 000 hour life span LED technology for years of maintenance free service. UL and DLC Listed.

FEATURES:

- **LED LIGHT PANELS** - LED Lay-in Light Panel Fixtures are a long life, energy efficient replacement for fluorescent fixtures. Designed for installation into 1X4-foot drop ceiling grids.
- **COLOR AND POWER SELECTABLE** - These fixtures allow you to choose the color temperature at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Super White depending on your preference using a switch located on the back. A second switch allows you to select between wattage for different lumen outputs. Choose 20 watts, 30 watts, or 40 watts.
- **DIMMABLE** - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10%.
- **LONG LIFE** - Provides up to 50, 000 hours energy efficient light. No maintenance, long-life LED technology means you won't need to climb ladders to replace difficult to reach bulbs.
- **UL Listed** - UL Listed for safety and quality. DLC listed for design and efficiency. Great for commercial or residential applications on 120/277 volt service.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	0-100%
Material	Aluminum
Lens Finish	White

Electrical Characteristics

Watts	20/30/40
Volts	100-277
LED Chip Manufacturer	4014
Power Factor	0.9
Temperature	+10 to +40 °C

Light Characteristics

Lumens Brightness	4320/4600/4400
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	120°

Fixture Characteristics

Style	Flat
Shape	Rectangle
Number of Lights	1
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	PJJ2K0RZ
DLC Classification	Standard

Product Dimensions

Size	1X4
Item Dimension (in)	(W) 11.81 (H) 0.39 (D) 47.8
Package Dimension (in)	(W) 4 (H) 49 (D) 14
Package Weight (lb)	0.05

Product Data

Case Unit Rate	1
Pack Size	2
Item UPC	653703854625
Warranty Years	5

ACCESSORIES:

Catalog # 89156-SU
EM