

Sunlite 85466 2-Foot LED Strip Light Fixture, Power Selectable 15W/20W/25W, Motion Sensor, 3250 Lumens, Color Selectable 30K/35K/40K/50K, Dimmable, ETL Listed, Built-In Battery Backup

DESCRIPTION:

Upgrade your lighting to the eco-friendly Sunlite 2-Foot LED Strip Light Fixture. The Bi-level PIR sensor allows the fixture to dim after motion is no longer detected. Choose between 10%, 20%, 30%, or 50% brightness for 30 seconds, 20 minutes, or until motion is detected again. This feature can also be deactivated. This fixture allows you to choose the color temperature and wattage at any time. Select 3000K, 3500K, 4000K or even 5000K depending on your preference using a switch located on the side of the fixture. Take control of the light emitted with its selectable wattage of 15W/20W/25W. This dimmable fixture long life provides 50,000 hours of maintenance-free service LED technology. Estimated annual energy costs of \$1.81 or \$2.41 or \$3.01 (Based on 3 Hrs/Day at \$0.11/kWh). Multi-volt of 120-277 and 80 CRI. In the event of a power outage this fixture will provide up to 90 minutes of light using the integrated battery. Battery charges/recharges automatically while power is on. ETL Listed for damp location installation. Ideal for Garage, Stairwells, Utility Room, Attics, Workshop, and more. Fixture Dimension: 23.9" L x 2.4" W x 3.2" H.

FEATURES:

- COLOR TEMPERATURE & POWER SELECTABLE This fixture allows you to choose the color temperature and wattage at any time. Select 3000K, 3500K, 4000K or even 5000K depending on your preference using a switch located on the side of the fixture. Take control of the light emitted with its selectable wattage of 55W/60W/65W.
- DIMMABLE & BI-LEVEL MOTION SENSOR The lighting output can be changed when connected to an LEDcompatible dimmer switch (0-10v), with a beam angle of 145 degrees, allowing it to adapt to any lighting to suit the mood. Bi-level PIR sensor allows the fixture to dim after motion is no longer detected. Choose between 10%, 20%, 30%, or 50% brightness for 30 seconds, 20 minutes, or until motion is detected again. This feature can also be deactivated.
- LONG LIFE LED This strip light produces a bright selectable color with a robust high lumen output that varies depending on the selected wattage, it can be 1950/2600/3250 lumens. This dimmable fixture long life provides 50,000 hours of maintenance-free service LED technology. Estimated annual energy costs of \$1.81 or \$2.41 or \$3.01 (Based on 3 Hrs/Day at \$0.11/kWh). Multivolt of 120-277 and 80 CRI.
- BUILT-IN BATTERY BACKUP In the event of a power outage this fixture will provide up to 90 minutes of light

sunlite

SPECIFICATIONS:

General Characteristics

Catalog # 85466-SU LFX/EC/2'/MW/4SCT/EM/BLS

General Characteristics		Product Dimensions	
Average Rated Hours	50000	Size	24"
Finish	White	Item Dimension (in)	(W) 2.4 (H) 3.2 (D) 23.9
Average Life Span Years	46	Package Dimension (in)	(W) 24.37 (H) 3.56 (D) 3
Dimmable	Yes	Package Weight (lb)	3.29
Dimming Type	0-10V Low Voltage	Product Data	
Dimming Percentage	10-100%		
Material	Iron & Acrylic	Case Unit Rate	6
Lens Material	PMMA	Item UPC	653703854663
Lens Finish	White	Warranty Years	5

Electrical Characteristics

Watts	15/20/25
Volts	120-277
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4°F - 104°F

Light Characteristics

Lumens Brightness	1950/2600/3250
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/35K/40K/50K
Beam Angle	110°
Flicker	No

Fixture Characteristics

Shape	Linear
Number of Lights	1
Mounting	Surface
Motion Sensor	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Number	S-XB0V3S
DLC Classification	Premium

744 Clinton Street Brooklyn, NY, 11231 | 718.768.7000