

Sunlite 85532 2-Foot LED Linear High Bay Fixtures with Acrylic Diffuser Lens, 130 Watts, Multi-Volt, 17680 Lumens, 5000K Daylight, 80 CRI, Dimmable, UL Listed, White, For Commercial & Residential Use
UFO

DESCRIPTION:

The 2-Foot LED Linear High Bay Fixtures with Acrylic Diffuser Lens from Sunlite are an energy efficient solution to your industrial lighting needs. Color temperature is 5000K Daylight with a bright 17680 lumen output while only using 130 watts of electricity. long, 50,000-hour lifespan means years of reliable and maintenance free service with no bulbs to replace. Estimated annual energy costs of \$15.66 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time. These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10% with 80 CRI. Listed for damp location installation. DLC Listed for design and quality. Designed for indoor use only. For use on 120/277-volt electrical systems. High lumen output designed for use in warehouses, commercial garages, workshops, factories, or any indoor industrial environment. Dimension: 12.99" W x 23.82" H x 3.64" D.

FEATURES:

- **UPGRADE TO LED** - Replace older high bay lights with energy efficient LEDs. These 2-Foot linear fixtures feature a durable and lightweight steel body designed for pendant mounting finished in white. Great for new installations, too.
- **SUPER WHITE LIGHT** - Color temperature is 5000K Daylight with a bright 17680 lumen output while only using 130 watts of electricity.
- **LONG LIFE SPAN** - A long, 50,000-hour lifespan means years of reliable and maintenance free service with no bulbs to replace. Estimated annual energy costs of \$15.66 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time.
- **DIMMABLE** - These fixtures can be dimmed when attached to a low voltage (0-10V) dimming control. Range is 100-10% with 80 CRI.
- **UL LISTED** - UL Listed for damp location installation. DLC Listed for design and quality. Designed for indoor use only. For use on 120/277-volt electrical systems. High lumen output designed for use in warehouses, commercial garages, workshops, factories, or any indoor industrial environment. Dimension: 12.99" W x 23.82" H x 3.64" D.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Material	Steel & Acrylic
Lens Finish	White

Electrical Characteristics

Watts	130
Volts	100-277

Light Characteristics

Lumens Brightness	17680
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K

Fixture Characteristics

Shape	Linear
Number of Lights	1
Mounting	Pendant
Fixture Technology	LED
Use Location	Indoor

Product Dimensions

Size	24"
Item Dimension (in)	(W) 12.99 (H) 23.82 (D) 3.64
Item Weight (lb)	7.65
Package Dimension (in)	(W) 24.8 (H) 13.48 (D) 4
Package Weight (lb)	7.65

Product Data

Item UPC	653703855325
Warranty Years	5

ACCESSORIES:

Catalog # 30580-SU
WIREGUARD

Catalog # 30574-SU
Surface