

U-Shaped

Sunlite 87908-SU LED T8 U-Bend Tube, Single End Bypass, 18 Watts, 50,000 Hour Lifespan, 2200 Lumens, Shatter Resistant, DLC Listed, 40K - Cool White 1 Pack

Bypass Single End | U-Bend Tube

DESCRIPTION:

Upgrade your T8 fluorescent U-Bend lamps with energy efficient LED single end bypass bulbs. These tubes are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you'll be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time. Ideal for ceiling fixtures, troffers, offices, or any fluorescent U-Bend fixtures in commercial locations. These fluorescent replacement LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions available online or consult an electrician for more information.

FEATURES:

- **UPGRADE TO LED** - Convert your existing T8 fluorescent U-Bend lamps to LED with these single end bypass bulbs. They are instant on at full brightness with no buzzing or flickering. Ideal for ceiling fixtures, troffers, offices, or any fluorescent U-Bend fixtures in commercial locations.
- **ENERGY EFFICIENT** - Each bulb puts out a bright 2200 lumens of light with a 4000K cool white color temperature while only using 18 watts of electricity. Annual energy costs are a low \$2.17 (Based on 3 hours/day at \$0.11/kWh).
- **LONG LIFE** - With a life span of up to 50,000 hours you'll be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time.
- **THE SAFER CHOICE** - These LED bulbs are UL Listed for damp location installation and have been tested to meet their rigorous safety standards. They are also DLC listed for quality and efficiency. And unlike fluorescent tubes, they contain no harmful chemicals and do not require special handling or disposal.
- **BALLAST BYPASS REQUIRED** - These fluorescent replacement LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions available online or consult an electrician for more information.



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	50000
Finish	White
Base	2x Medium 2-Pin (2G13)
Average Life Span Years	46
Dimmable	No
Material	Plastic

Electrical Characteristics

Watts	18
Volts	120-277
Equivalent Wattage	T8 U & T12 U
Power Factor	0.9
Temperature	-20° to 45° C

Light Characteristics

Lumens Brightness	2200
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Beam Angle	210°

Additional Features

Safety Rating Mark	UL Classified - Damp Location
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PL093AYEP8LV
DLC Classification	Standard

Product Dimensions

MOL (in)	22.8
Item Dimension (in)	(W) 7 (H) 0.96 (D) 22.25
Item Weight (lb)	0.400
Package Dimension (in)	(W) 7.28 (H) 1.25 (D) 22.8
Package Weight (lb)	0.850

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703879086
Warranty Years	5
Package Type	Box