

Sunlite 88169-SU LED Outdoor Mini Wall Pack Light Fixture, 25 Watts (200W Equivalent), 120-277 Volts, 3000 Lumens, Built-In Photocell, 50,000 Hour Life Span, ETL & DLC Listed, 3000K Warm White

DESCRIPTION:

Sunlite 25 Watt LED Mini Wall Pack light fixtures are designed to provide ample outdoor illumination. These wall mount fixtures provide a bright 3000 lumen output at 3000K warm white color temperature. Equivalent to a 200 watt light. They feature a built-in photocell for automatic dusk to dawn operation. With 54 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours. Each fixture uses only 25 watts of electricity and has a low estimated yearly energy cost of \$3.01. (Based on 3 hours/day use at \$0.11/kWh) The weatherresistant aluminum body is finished in bronze and houses a durable frosted polycarbonate lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed. For use with 120-277 volt electrical service. ETL Listed for safety and DLC Listed for quality and efficiency. 70 CRI. IP65 Rated. Fixture measures 8.22 inches high, 5.54 inches wide, 3.39 inches deep.

FEATURES:

- LED TECHNOLOGY Sunlite LED Mini Wall Pack light fixtures are designed to provide ample outdoor illumination. With 54 built-in LEDs they are an energy efficient and maintenance-free lighting solution with a long life span of up to 50,000 hours.
- ENERGY EFFICIENT Using only 25 watts of energy these fixtures have a low estimated yearly energy cost of \$3.01. (Based on 3 hours/day use at \$0.11/kWh) These fixtures will provide significant savings in electricity over their lifetime with no bulbs to replace.
- BUILT-IN PHOTOCELL Built-in photocell for automatic dusk to dawn operation. They provide a bright 3000 lumen output at 3000K warm white color temperature. Equivalent to a 200 watt light.
- MULTIPLE OUTDOOR USES These commercial grade fixtures feature a weather-resistant aluminum body finished in bronze and house a durable frosted polycarbonate lens. Ideal for security and general purpose lighting along the perimeter of buildings, entryways or anywhere extra lighting is needed.
- ETL AND DLC LISTED These fixtures are ETL Listed for safety and DLC Listed for quality and efficiency. They operate on 120-277 volt service. 70 CRI. IP65 Rated. Fixture measures 8.22 inches high, 5.54 inches wide, 3.39 inches deep.



SPECIFICATIONS:

General Characteristics

Average Rated Hours

Finish

Bronze

Average Life Span Years

Dimmable

Material

Lens Finish

50000

Bronze

46

No
aluminum
Frosted

Electrical Characteristics

Watts 25
Volts 120-277
Equivalent Wattage 70-100W
LED Chip Manufacturer Philips 2835
Power Factor 0.95
Temperature -40 - 40

Light Characteristics

Lumens Brightness3000Color Rendering Index CRI70Emitted ColorWarm WhiteColor Temperature Kelvin3000KBeam Angle120°

Fixture Characteristics

ShapeRectangleNumber of Lights1MountingWallPhoto ControlYesFixture TechnologyLEDUse LocationOutdoor

Additional Features

Safety Rating Mark
Safety Rated For Canada
Yes
Safety Rated For USA
Yes
DLC
Yes
DLC Classification
Standard

Product Dimensions

Item Dimension (in)
Package Dimension (in)
Package Weight (lb)
Cord Length

Product Data

Case Unit Rate Item UPC Warranty Years (W) 5.54 (H) 8.22 (D) 3.39 (W) 8.6 (H) 5.8 (D) 3.8 0.18009 2"

10

653703881690

5