

Plug-In

Sunlite 88213-SU LED PLV Plug and Play Light Bulb, 9 Watts (26W Equivalent), G24q Base, Ballast Dependent, CFL Replacement, UL Listed, 40K - Cool White 1 Pack

Plug and Play | Vertical

DESCRIPTION:

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED plug and play bulbs from Sunlite. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Provides up to 50,000 hours of energy efficient light so you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation. These 4-Pin base (G24q) plug and play bulbs do not require a ballast bypass. For use with electronic ballasts only. See manufacturer's website for a complete list of compatible ballasts.

FEATURES:

- UPGRADE TO LED Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED plug and play bulbs from Sunlite. They feature a 4-Pin base (G24Q) and are instant on at full brightness with no buzzing or flickering. Ideal for use in recessed lighting, lamps or any compatible fixture.
- PLUG AND PLAY These bulbs are direct replacements for PL fluorescent bulbs with no bypass required. For use with electronic ballasts only. See manufacturer's website for a complete list of compatible ballasts.
- ENERGY EFFICIENT These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. 1000 Lumen output with a color temperature of 4000K (cool white). Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- LONG LIFE SPAN Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- A SAFER CHOICE Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.



sunlite

SPECIFICATIONS:

General Characteristics

Product Dimensions

Bulb Shape	PLV	MOL (in)	4.66
Average Rated Hours	50000	Item Dimension (in)	(W) 1.79 (H) 1.79 (D) 4.64
Finish	White	ltem Weight (lb)	0.840
Base	4-Pin (G24q)	Package Dimension (in)	(W) 1.95 (H) 2 (D) 5.9
Average Life Span Years	46	Package Weight (lb)	0.240
Dimmable	No	Product Data	
Material	Aluminum & Plastic		
		Case Unit Rate	12
Electrical Characteristics		Pack Size	1

Item UPC

Warranty Years Package Type

Electrical Characteristics

Watts	9
Equivalent Wattage	18
Power Factor	0.9
Temperature	-20-45?

Light Characteristics

Lumens Brightness	1000
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Flicker	<30%

Additional Features

Safety Rating Mark	UL Listed
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PLE5AW71FC6X
DLC Classification	Standard

12
1
653703882130
5
Box

Catalog # 88213-SU PLV/E/LED/IS/9W/40K/V2