

Plug-In

Sunlite LED PLD Ballast Dependable 9W (PLD 26W Equivalent) Light Bulb G24q Base, Cool White

Ballast Dependable

DESCRIPTION:

Sunlite Lighting's LED PLD lamps deliver a comfortable but vivid and flicker-free ray of light to any setting. Consuming only 9 watts of energy to produce a stunning 4000K Cool White light in addition to offering significant energy savings when compared to competing bulbs. Ideal for various settings while not utilizing any hazardous material and chemicals, such as fragile glass and Mercury. Featuring a (G24q) base, Sunlite's plug-in lamps are designed to fit in a variety of applications. With an average lamp life of 50000 hours, Sunlite Lighting's PLD bulbs do more than just illuminate a room; these bulbs add a layer of life to any and all décor.

FEATURES:

- This 270° beam spread PLD lamp produces an efficient 4000K Cool White beam of light at a powerful 900 lumens
- On average, this LED plug-in lamp lasts an astonishing 50000 hours and features 33 energy saving diodes
- Compatible with all four/quad pin bases
- Noticeably lower electricity usage and cost by replacing a PL fluorescent lamp with Sunlite's LED PLD lamp that only consumes 9W
- Premium-quality, energy saving, modern replacement LED PL plug-in lamp sold at a consumer friendly price

sunlite

SPECIFICATIONS:

General Characteristics

Average Rated Hours

Average Life Span Years

Electrical Characteristics

Bulb Shape

Dimmable

Base

Watts

PLD 50000 4-Pin LED Base (G24q) 46 No

9

900

82

Cool White

4000K 270°

Product Dimensions

MOL (in)	6.61
Diameter (in)	1.1
Item Dimension (in)	(W) 1.1 (H) 6.6 (D) 1.1
Item Weight (lb)	0.150
Package Dimension (in)	(W) 1.5 (H) 6.7 (D) 1.6
Package Weight (lb)	0.200

Product Data

26	Case Unit Rate	12
Epistar 2835	Pack Size	1
0.9	Item UPC	653703882727
	Package Type	Box

Light Characteristics

Equivalent Wattage LED Chip Manufacturer

Power Factor

Lumens Brightness **Color Rendering Index CRI Emitted Color** Color Temperature Kelvin **Beam Angle**

Additional Features

Safety Rating Mark DLC **DLC Number DLC Classification**

UL Listed - Damp Location Yes PRTWHYR6 Standard

6.61
1.1
(W) 1.1 (H) 6.6 (D) 1.1
0.150
(W) 1.5 (H) 6.7 (D) 1.6
0.200