

Plug-In

Sunlite 88273-SU LED PLD Light Bulb, 9 Watts (26W Equivalent), 1000 Lumens, G24q Base, Ballast Dependant, CFL Replacement, UL Listed, 40K - Cool White 1 Pack

Plug and Play

DESCRIPTION:

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 1000 lumen with 4000K color temperature at 4000K. Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.

FEATURES:

- **UPGRADE TO LED** - Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage.
- **NO FLICKERING OR BUZZING** - LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 1000 lumen with Cool White color temperature at 4000K.
- **ENERGY EFFICIENT** - These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. That's a 65% energy savings. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- **LONG LIFE SPAN** - Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- **A SAFER CHOICE** - Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.



SPECIFICATIONS:

General Characteristics

Bulb Shape	PLD
Average Rated Hours	50000
Finish	White
Base	4-Pin (G24q)
Average Life Span Years	46
Dimmable	No
Material	Aluminum & Plastic

Electrical Characteristics

Watts	9
Equivalent Wattage	18
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	1100
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Beam Angle	270°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PL6L6MT5JDSD
DLC Classification	Standard

Product Dimensions

MOL (in)	6.57
Item Dimension (in)	(W) 1.4 (H) 6.61 (D) 1.4
Item Weight (lb)	0.170
Package Dimension (in)	(W) 1.42 (H) 6.76 (D) 1.44
Package Weight (lb)	0.210

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703882734
Warranty Years	5
Package Type	Box