

Sunlite 88335 12" Decorative Flushmount Ceiling Fixture, 15 Watts, 1050 Lumens, 3000K Warm White, Dimmable, 80 CRI, UL Listed, Brushed Nickel, For Entryways, Hallways & Residential Use

DESCRIPTION:

Sunlite's LED decorative flushmount ceiling fixture feature a stylish design with a clean appearance This decorative ceiling fixture is a simple, economical solution for your indoor lighting needs. It features a brushed nickel finish and adds a touch of elegance to any rooms decor. Built-in long-life LED technology means 50,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. Estimated annual energy costs of \$1.81 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. The fixture can be dimmed when installed with an LED-compatible dimmer. High color rendering at 80 CRI. Tested Compatible Dimmers: Lutron LGCL-153PL, MACL-153M, DV-600P, DVCL-153P, AYCL-153P, TG-600PH-WH, SCL-153P, CT-600P, FS-5FH-DK, TGCL-153PH, DVW-600PH-WH & Leviton 6633, 6672. This fixture is UL Listed for wet location installation rated and made with steel and acrvlic. Ideal for Entryways. Bedrooms. Kitchens, Hallways, Bathroom and Residential Use. Dimension 8.1" W x 3.08" H x 6" D.

FEATURES:

- TRADITIONAL DESIGN This decorative ceiling fixture is a simple, economical solution for your indoor lighting needs. It features a brushed nickel finish and adds a touch of elegance to any rooms decor.
- LONG LIFE LED Built-in long-life LED technology means 50,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. Estimated annual energy costs of \$1.81 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates.
- EASY INSTALLATION These ceiling fixtures can be easily mounted to a standard junction box. Installation hardware and instructions are included.
- DIMMABLE LED The fixture can be dimmed when installed with an LED-compatible dimmer. High color rendering at 80 CRI. Tested Compatible Dimmers: Lutron LGCL-153PL, MACL-153M, DV-600P, DVCL-153P, AYCL-153P, TG-600PH-WH, SCL-153P, CT-600P, FS-5FH-DK, TGCL-153PH, DVW-600PH-WH & Leviton 6633, 6672
- UL LISTED This fixture is UL Listed for wet location installation rated and made with steel and acrylic. Ideal for Entryways, Bedrooms, Kitchens, Hallways, Bathroom and Residential Use. Dimension 8.1" W x 3.08" H x 6" D.

sunlite

SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Average Life Span Years Dimmable **Dimming Type**

Dimming Percentage Material Lens Finish **Bulb Type** Application

Electrical Characteristics

Watts	15
Volts	120
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-20° to 45°

Light Characteristics

Lumens Brightness	1050
Color Rendering Index CRI	80
R9 Rating	13
Emitted Color	Warm White
Color Temperature Kelvin	3000K

Fixture Characteristics

Style	
Shape	
Number of Lights	
Mounting	
Fixture Technology	
Use Location	

Additional Features

Safety Rating Mark Safety Rated For Canada Yes Safety Rated For USA Yes

Integrated LED 50000 Brushed Nickel 46 Yes Forward Phase (Triac or Incandescent) 10-100% Steel & Acrylic White Integrated Residential

Product Dimensions

Size	12"
MOL (in)	3.5
Diameter (in)	12.04
Item Dimension (in)	(W) 12.04 (H) 3.5 (D) 12.04
Item Weight (Ib)	3.1
Package Dimension (in)	(W) 13.2 (H) 5 (D) 5
Package Weight (lb)	3.1
i achage weight (ib)	0.1

Product Data

Case Unit Rate Item UPC Warranty Years 6 653703883359 З

UL Listed - Damp Location

Traditional Round 1 Surface LED Indoor





Catalog # 88335-SU LFX/DCO12/BN/15W/D/30K