

#### Par Series

## Sunlite 88398-SU LED PAR38 Reflector Bulb, 18 Watts (120W Equivalent), Medium Base (E26), Dimmable, 1350 Lumens, ETL Listed, 65K - Daylight 1 Pack

High Efficiency

### DESCRIPTION:

These indoor PAR38 light bulbs provide an energy efficient replacement for older incandescent and halogen bulbs with a medium (E26) base. They use only 18 watts of electricity while providing the same amount of light as a 120 watt incandescent bulb. Their long life means replacing difficult to reach bulbs less often saving you time and money. They are dimmable (100%-5%) and cool to the touch when lit. Perfect for recessed lighting, track lighting, and other indoor lighting fixtures. Compatible Dimmers: Leviton: 6161, 6681, IPE04, IPI06, IPL06, RTD01-10ZLutron: CTCL-153P, CTELV-303P, DV-603P, DVCL-153P, DVELV-303P, IPX10-1, LGCL-153P, LGCL-153PL, MAELV-600, NTLV-600, RRD-6NA, S-600P, S-603P, SELV-300P, SLV-600P, VTELV-600M

### FEATURES:

- **UPGRADE TO LED** - These dimmable, 18 watt PAR38 LED light bulbs are an energy efficient replacement for 120 watt incandescent bulbs. They have a medium (E26) base and remain cool to the touch even when lit. 35 degree beam angle and instant-on at full 1350 lumen brightness.
- **SAVE ENERGY** - Get the same light output of a 120 watt incandescent bulb while saving 85% on electricity. The annual energy cost is a low \$2.17 (Based on 3 hours/day at \$0.11 per/kWh).
- **LONG LIFE SPAN** - With an average life span of 25,000 hours you'll need to replace hard to reach bulbs less often. Perfect for recessed lighting, track lighting, and other indoor lighting fixtures.
- **DAYLIGHT COLOR TEMPERATURE** - At 6500K the lighting temperature of these super white LED fixtures provide ample task lighting for kitchens, study areas, offices, showrooms, workshops or anywhere you need bright light. 80 CRI.
- **THE SAFER CHOICE** - These indoor bulbs are ETL Listed for damp location installation. Ideal for both residential and commercial use. IP20 Rated.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	PAR38
<b>Average Rated Hours</b>	25000
<b>Base</b>	Medium Screw (E26)
<b>Average Life Span Years</b>	23
<b>Dimmable</b>	Yes
<b>Material</b>	Aluminium & Plastic

### Electrical Characteristics

<b>Watts</b>	18
<b>Volts</b>	120
<b>Equivalent Wattage</b>	120
<b>LED Chip Manufacturer</b>	Bridgelux
<b>Power Factor</b>	0.7
<b>Temperature</b>	-20° to 45° C

### Light Characteristics

<b>Lumens Brightness</b>	1350
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Daylight
<b>Color Temperature Kelvin</b>	6500K
<b>Beam Angle</b>	35°

### Additional Features

<b>Safety Rating Mark</b>	ETL - Damp Location
<b>CE Certified</b>	Yes

### Product Dimensions

<b>MOL (in)</b>	4.96
<b>Diameter (in)</b>	4.76
<b>Item Dimension (in)</b>	(W) 4.69 (H) 5.15 (D) 4.69
<b>Item Weight (lb)</b>	0.400
<b>Package Dimension (in)</b>	(W) 5 (H) 5.5 (D) 5
<b>Package Weight (lb)</b>	0.56

### Product Data

<b>Case Unit Rate</b>	6
<b>Pack Size</b>	1
<b>Item UPC</b>	653703883984
<b>Warranty Years</b>	3
<b>Package Type</b>	Box