

ST Series

Bypass Dual End

DESCRIPTION:

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

FEATURES:

-
-
-
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	50000
Finish	White
Base	Medium 2-Pin (G13)
Average Life Span Years	46
Dimmable	No
Material	Glass

Electrical Characteristics

Watts	9
Volts	120-277
Equivalent Wattage	F17T8, F20T12
Power Factor	0.9
Temperature	-20° to 45°

Light Characteristics

Lumens Brightness	1150
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Additional Features

Safety Rating Mark	UL Classified - Damp Location
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PLJPBUTHF436
DLC Classification	Standard

Product Dimensions

Size	2 Foot
MOL (in)	23.22
Diameter (in)	0.98
Package Dimension (in)	(W) 23.75 (H) 1.02 (D) 1.02
Package Weight (lb)	0.240

Product Data

Case Unit Rate	25
Pack Size	1
Item UPC	653703884318
Warranty Years	5
Package Type	Sleeve