

ST Series

Sunlite 88475 LED T8 Ballast Bypass Light Tube (Type B) 4 Foot, 17W (F32T8 Equal), 2200 Lm, Medium G13 Base, Frosted, Dual End Connection, UL Listed, 4000K Cool White, 25 Count

Bypass Dual End

DESCRIPTION:

Upgrade your T8 fluorescent bulbs with LED energy efficient ballast bypass bulbs. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 50,000 hours you will be required to replace difficult to reach bulbs less often. You'll save maintenance costs and save energy at the same time. These bulbs can be used for both commercial and residential locations. They are UL Listed for damp location use. Unlike fluorescent tubes, they contain no harmful chemicals and do not require special handling or disposal.



FEATURES:

- **UPGRADE TO LED** - Replace your inefficient T8 fluorescent bulbs with energy saving LED bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. Glass outer tubes prevent yellowing and bending over time. High Color Rendering Index (CRI) rating of 82
- **BALLAST BYPASS REQUIRED** - These bulbs are direct replacements for 4 foot T8 G13 Bi-Pin base fluorescent tubes. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions can be found online or consult an electrician for more information
- **ENERGY EFFICIENT** - Each bulb puts out a bright 2200 lumens of light with a 4000K cool white color temperature while only using 17 watts of electricity. Annual energy costs are a low \$2.05 (Based on 3 hours/day at \$0.11/kWh)
- **LONG LIFE** - With a life span of up to 50,000 hours you'll be required to replace difficult to access bulbs less often. You will save maintenance costs and save energy at the same time
- **UL & DLC LISTED** - These shatterproof led bulbs are UL Listed and have been tested to meet their rigorous safety standards. They are also DLC listed for quality and efficiency. Unlike fluorescent tubes, led tubes contain no harmful chemicals and do not require special handling or disposal

SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	50000
Finish	White
Base	Medium 2-Pin (G13)
Average Life Span Years	46
Dimmable	No
Material	Plastic

Electrical Characteristics

Watts	17
Volts	120-277
Equivalent Wattage	F28T5, F32T8, F40T12
LED Chip Manufacturer	Type B
Power Factor	0.9
Temperature	-20° to 45°

Light Characteristics

Lumens Brightness	2200
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Beam Angle	210°

Additional Features

Safety Rating Mark	UL Listed - Damp Location
UL Rated Enclosed Fixtures	Yes
DLC	Yes
DLC Number	PLR3ANSL2ANI
DLC Classification	Standard

Product Dimensions

MOL (in)	47.67
Item Dimension (in)	(W) 1 (H) 1 (D) 48
Package Dimension (in)	(W) 6 (H) 6 (D) 49
Package Weight (lb)	12.96

Product Data

Case Unit Rate	25
Pack Size	1
Item UPC	653703884752
Warranty Years	5
Package Type	Sleeve