

**Sunlite 88478 3-Inch AC LED Light
Engine Module, 10 Watts (60W=), 700
Lumens, 3000K Warm White, 90 CRI,
Dimmable, 25,000 Hours Life Span,
120v, UL Listed**

DESCRIPTION:

Sunlite's AC LED Light Engine Module allow you to convert your existing light fixtures into state of the art LED fixtures. These LED engines can be used to upgrade a variety a different fixture types in your home or business. For use with ceiling fixtures and ceiling fans in bedrooms, hallways, stairwells, closets, basements, garages, storage areas, porches and more. Suitable for damp location installation. Can be screwed directly to round or square flat-base fixtures. With an average life span of 25,000 hours these units will last up to 22.8 years based on 3 hours per day usage. Saves the nuisance and cost of replacing hard to reach bulbs. These LED retrofit panels can be dimmed when installed with a Forward Phase (Triac or Incandescent) dimmer. UL Listed for safety and quality. High color rendering index of 90 (CRI). Dimension: 0.76" H x 3.3" W x 0.76" D.

FEATURES:

- **UPGRADE TO LED** - Keep your existing decorative fixtures and upgrade to energy efficient LED technology. Simple wiring for easy installation. These LED modules can be mounted with center threaded screw type fixtures or directly to flat fixture bases with mounting screws. Commercial grade with a heavy-duty metal base. Can also be used to replace fluorescent Circline bulbs. (Ballast bypass required)
- **MULTIPLE APPLICATIONS** - These LED engines can be used to upgrade a variety a different fixture types in your home or business. For use with ceiling fixtures and ceiling fans in bedrooms, hallways, stairwells, closets, basements, garages, storage areas, porches and more. Can be screwed directly to round base fixtures.
- **LONG-LIFE TECHNOLOGY** - With an average life span of 25,000 hours these units will last up to 22.8 years based on 3 hours per day usage. Saves the nuisance and cost of replacing hard to reach bulbs.
- **DIMMABLE** - These LED retrofit panels can be dimmed when installed with a Forward Phase (Triac or Incandescent) dimmer.
- **UL LISTED** - UL Listed for safety and quality. High color rendering index of 90 (CRI). Dimension: 0.76" H x 3.3" W x 0.76" D.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	25000
Finish	White
Average Life Span Years	23
Dimmable	Yes
Dimming Percentage	10-100%
Material	Aluminum
Lens Material	Polycarbonate
Lens Finish	Clear

Electrical Characteristics

Watts	10
Volts	120
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	0°F - 104°F

Light Characteristics

Lumens Brightness	700
Color Rendering Index CRI	90
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	120°
Flicker	<10%

Fixture Characteristics

Mounting	Other
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed
Energy Star	Yes
Energy Star Number	2355917

Product Dimensions

Size	3"
Item Dimension (in)	(W) 3.3 (H) 0.76 (D) 0.76
Package Dimension (in)	(W) 1.2 (H) 4.2 (D) 4.1
Package Weight (lb)	0.4

Product Data

Case Unit Rate	60
Item UPC	653703884783
Warranty Years	5

