

ED Series

Sunlite 03650-SU MH150/U/MED M102 Metal Halide Lamp, 150 Watts, Pulse Start, Medium Base (E26), ED17, 15,000 Hours Life, 14000 Lumen, Clear Finish, 4000K

Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 150 watt metal halide bulbs have a bright 14000 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code M102. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.19 inches in diameter, 5.41 inches tall.

FEATURES:

- **METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 150 watt bulb puts out a bright 14000 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MEDIUM BASE** - Standard medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.19 inches diameter, 5.41 inches tall.
- **PULSE START** - These bulbs feature pulse start for quicker startup, less lumen depreciation, long 15,000 hour average lifespan, and more lumens per watt so you save energy.
- **ANSI CODE M102** - This metal halide bulb is for use in M102 ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED17
Ansi code	M102
Average Rated Hours	15000
Finish	Clear
Base	Medium Screw (E26)
Average Life Span Years	14

Electrical Characteristics

Watts	150
Volts	95

Light Characteristics

Lumens Brightness	14000
Color Rendering Index CRI	65
Coating	Uncoated
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Product Dimensions

MOL (in)	5.295
Diameter (in)	2.198"
Item Dimension (in)	(W) 2.19 (H) 5.41 (D) 2.19
Package Dimension (in)	(W) 2.4 (H) 6 (D) 2.4
Package Weight (lb)	0.200

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703036502
Warranty Years	1