

## ED Series

### Sunlite 03658-SU MH250/U/MOG M58 Metal Halide Lamp, 250 Watts, Mogul Base (E39), ED28, 15,000 Hour Life Span, 21000 Lumen, Clear Finish, 4000K

Metal Halide

#### **DESCRIPTION:**

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 250 watt metal halide bulbs have a bright 21000 lumen output. They are mogul base (E39), ED28 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code M58. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 3.53 inches in diameter, 8.19 inches tall.

#### **FEATURES:**

- **METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 250 watt bulb puts out a bright 21000 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MOGUL BASE** - Larger mogul base (E39) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 3.53 inches diameter, 8.19 inches tall.
- **LONG LIFE** - These probe start bulbs feature a long 15,000 hour average lifespan.
- **ANSI CODE M58** - This metal halide bulb is for use in M58 ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	ED28
<b>Ansi code</b>	M58
<b>Average Rated Hours</b>	15000
<b>Finish</b>	Clear
<b>Base</b>	Mogul Screw (E39)
<b>Average Life Span Years</b>	14

### Electrical Characteristics

<b>Watts</b>	250
<b>Volts</b>	120

### Light Characteristics

<b>Lumens Brightness</b>	21000
<b>Color Rendering Index CRI</b>	65
<b>Coating</b>	Uncoated
<b>Emitted Color</b>	Cool White
<b>Color Temperature Kelvin</b>	4000K

### Product Dimensions

<b>MOL (in)</b>	8.237
<b>Diameter (in)</b>	3.56"
<b>Item Dimension (in)</b>	(W) 3.53 (H) 8.19 (D) 3.53
<b>Item Weight (lb)</b>	0.330
<b>Package Dimension (in)</b>	(W) 3.8 (H) 9.5 (D) 3.8
<b>Package Weight (lb)</b>	0.500

### Product Data

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	1
<b>Item UPC</b>	653703036588
<b>Warranty Years</b>	1