

ED Series

**Sunlite 03664-SU MP100/U/MED M155/O
Protected Metal Halide Lamp, 400 Watts,
Mogul Base (E39), ED37, Pluse Start,
15,000 Hours Life, 33000 Lumen, Clear
Finish, 4000K**
Protected Metal Halide

DESCRIPTION:

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. Energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 400 watt protected pulse start metal halide bulbs have a bright 33000 lumen output. They are mogul base (E39), ED37 bulbs with an average life span of 15,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, wall packs, and other commercial and industrial lighting applications. ANSI Code M155/O. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 4.7 inches in diameter, 11 inches tall.

FEATURES:

- **PROTECTED METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 400 watt bulb puts out a bright 33000 lumens of light. Color temperature is 4000K. Clear glass bulb.
- **MOGUL BASE** - Larger mogul base (E39) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 4.7 inches diameter, 11 inches tall.
- **PULSE START** - These protected pulse start bulbs feature a long 15,000 hour average lifespan.
- **ANSI CODE M155/O** - This metal halide bulb is for use in M155/O ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



SPECIFICATIONS:

General Characteristics

Bulb Shape	ED37
Ansi code	M155/O
Average Rated Hours	15000
Finish	Clear
Base	Mogul Screw (EX39)
Average Life Span Years	14

Electrical Characteristics

Watts	400
-------	-----

Light Characteristics

Lumens Brightness	33000
Mean Lumens	33000
Color Rendering Index CRI	65
Coating	Uncoated
Emitted Color	Cool White
Color Temperature Kelvin	4000K

Product Dimensions

MOL (in)	11
Diameter (in)	4.7
Item Dimension (in)	(W) 4.7 (H) 11 (D) 4.7
Package Dimension (in)	(W) 4.9 (H) 4.9 (D) 11.4
Package Weight (lb)	0.900

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703036649
Warranty Years	1

VARIATIONS:



03664-SU



03646-SU



03651-SU



03659-SU



03638-SU



03641-SU

Item Number	Description	Watts	Lumens	CRI	Kelvin Color	Hours	Pack
03664-SU	MP400/U/PS	400	33000	65	4000K CW	15000	1
03646-SU	MP100/U/MED/PS	100	8500	65	4000K CW	15000	1
03651-SU	MP150/U/MED	150	13300	65	4000K CW	15000	1
03659-SU	MP250/U/PS	250	23800	65	4000K CW	15000	1
03638-SU	MP50/U/MED/PS	50	3200	65	4000K CW	10000	1
03641-SU	MP70/U/MED	70	5600	65	4000K CW	15000	1