

**Sunlite 89308 LED Canless 3.5"
Recessed Light Fixture, 8 Watts (75W=),
700 Lumens, 80 CRI, Dimmable, 38°
Flood Beam, 30° Tilt, White Finish, 3000K
Warm White, IP44, ETL Listed for Damp
Location**

DESCRIPTION:

Sunlite LED 3.5-Inch Canless Downlight Fixtures are simple to install with no recessed can necessary. design with 360 degree rotation and up to 30 degree tilt allows you to direct the light where you need it. It features a 38 degree flood beam angle and faceted reflector for uniform light output at 3000K warm white color temperature. Dimmable when attached to an LED compatible dimmer switch. Built-in energy efficient LEDs with a long 50,000 hour lifespan for years of maintenance-free service. Uses only 8 watts of electricity while putting out as much light as a 75 watt bulb (700 lumens). Estimated annual energy costs is a low \$0.97 (Based on 3hr/day at \$0.11/Kwh). IC Rated with a built-in die cast aluminum heat sink. ETL Listed for damp location installation (IP44 Rated). For use indoors on 120 volt service. Junction box included. Ideal for commercial or residential use. Fixture measures 3.75 inches in diameter by 2.00 inches high. Junction box measures 2.44 inches wide by 4.02 inches deep by 1.50 inches high.

FEATURES:

- **CANLESS RECESSED LIGHTING** - Sunlite LED 3.5-Inch Canless Downlight Fixtures are simple to install with no recessed can necessary. IC rated with a built-in die cast heat sink for optimal safety.
- **DIMMABLE** - Light can be dimmed with attached to an LED compatible dimmer switch. Ideal for commercial or residential installations.
- **ENERGY EFFICIENT LEDS** - Built-in energy efficient LEDs with a long 50,000 hour lifespan for years of maintenance-free service. Uses only 8 watts of electricity while putting out as much light as a 75 watt bulb (700 lumens). Estimated annual energy costs is a low \$0.97 (Based on 3hr/day at \$0.11/Kwh).
- **ETL LISTED** - ETL Listed for damp location installation (IP44 Rated). For use indoors on 120 volt service. Junction box included. Fixture measures 3.75 inches in diameter by 2.00 inches high. Junction box measures 2.44 inches wide by 4.02 inches deep by 1.50 inches high.
-

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	Forward Phase (Triac or Incandescent)
Dimming Percentage	5-100%
Material	Aluminum & Plastic
Lens Finish	Clear

Electrical Characteristics

Watts	8
Volts	120
LED Chip Manufacturer	CXA1507
Power Factor	0.9
Temperature	-20-40°

Light Characteristics

Lumens Brightness	700
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	38°

Fixture Characteristics

Shape	Round
Number of Lights	1
Mounting	Recessed
IC Rating	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL - Damp Location
Safety Rated For Canada	Yes

Product Dimensions

Size	3.5"
MOL (in)	1.95
Diameter (in)	3.54
Package Dimension (in)	(W) 3.5 (H) 6.2 (D) 6.3
Package Weight (lb)	1.250

Product Data

Case Unit Rate	30
Item UPC	653703893082
Warranty Years	5