


INSTALLATION INSTRUCTIONS

FOR CEILING CIRCLINE MUSROOM MOUNT FIXTURES



READ INSTRUCTIONS AND REVIEW ALL DIAGRAMS BEFORE INSTALLING FIXTURE

GENERAL INSTRUCTIONS:

- 1. All electrical connections must be in accordance with local codes, ordinances and the National Electric Code.
- 2. These fixtures should be mounted on electrical outlet box. The box must be directly supported by the building structures.
- 3: Turn off the circuit breaker or remove the appropriate fuse to disconnect power source before installing fixture.
- 4. Turning the light switch off to cut the power is not sufficient to prevent electric shock.

TO INSTALL:

Turn electricity off at fuse box by removing fuse or turning the circuit breaker off.

- 1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring form the outlet box.
- 2. Using the diagram to the right as a mounting guide, mount the fixture*.

ELECTRICAL CONNECTION:

Connect the white wire(s) from the fixture to the white wire in the supply circuit. Connect the black wire(s) from the fixture to the black wire in the supply circuit. If your fixture is supplied with an appliance cord, connect the ribbed half to the white wire in the supply circuit. Connect the smooth half to the black wire in the supply circuit. Use CSA and UL listed wire connectors suitable for the size, type and number of conductors. Make sure there are no loose strands or wires. Secure wires with CSA and UL listed electrical tape. Connect both the ground wire from the fixture and the ground wire in the supply circuit to the ground terminal of the crossbar or back plate.

TO ASSEMBLE:

- 1. Spread the electrical splices to the black wires on one side of the outlet box, the white wires on the other.
- 2. Install light bulbs (not included).
- 3. Turn power on and make sure the light fixture is working properly.