Color Selectable

sunlite



Available Wattage 9W/11W/15W

SUPER BRIGHT 800 / 1100 / 1600 LM

Medium Screw (E26) Base



Built-in toggle allows selection among five color temperatures. (2700K, 3000K, 4000K, 5000K, 6500K)



Fewer SKUs, Save Stocking Spaces !

Eliminates the need to stock separate bulbs for each color temperature.

Transform the ambiance of any space with the Adjustable White 100-watt equivalent A19 LED bulb from Sunlite. Featuring a convenient built-in toggle, this bulb allows you to select from five distinct color temperatures—2700K Warm White, 3000K Neutral White, 4000K Cool White, and 5000K Super White 6500K Day Light—ensuring perfect lighting for any occasion. Whether you're looking to energize your morning, enhance focus during the day, or create a calming atmosphere in the evening, this versatile bulb has you covered.



1 PACK BOX

4 PACK BOX

| ltem# | Description | Watt | Eq. W | Lumen | LPW | CRI | Lens | Kelvin | Hours | Mol (in) | Features | CTN |
|--------------------------------|------------------------------------|------|-------|-------|-----|-----|-------|---------------------|-------|----------|----------|-----|
| 60 Watt Equivalent Dimmable | | | | | | | | | | | | |
| 80560-SU | A19/LED/9W/5SCT | 9 | 60 | 800 | 89 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| 80563-SU | A19/LED/9W/5SCT/ <mark>4PK</mark> | 9 | 60 | 800 | 89 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| 60 Watt Equivalent Dimmable | | | | | | | | | | | | |
| 80561-SU | A19/LED/11W/5SCT | 11 | 75 | 1100 | 100 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| 80564-SU | A19/LED/11W/5SCT/ <mark>4PK</mark> | 11 | 75 | 1100 | 100 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| 100 Watt Equivalent Dimmable | | | | | | | | | | | | |
| 80562-SU | A19/LED/15W/5SCT | 15 | 100 | 1600 | 107 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| 80565-SU | A19/LED/15W/5SCT/4PK | 15 | 100 | 1600 | 107 | 90 | White | 27K/30K/40K/50K/65K | 15000 | 4.29 | DL,DIM | 6 |
| | | | | | | | | | | | | |

DIM = Dimmable **DL** = Rated Damp Location