

#### **T** Series

Hybrid Type A + B

# **DESCRIPTION:**

Highlighting a dedication to quality and integrity, the Sunlite product line includes light bulbs of LED, linear fluorescent, compact fluorescent, incandescent, HID metal halide, halogen, decorative, and specialty lamps. In addition, the Sunlite line includes various indoor and outdoor commercial, Industrial, and residential fixtures. Electrical products include extension cords, socket adapters, wall plates, receptacles and switches, dimmers, timers, surge protectors, and much more.

## FEATURES:

- .
- -
- -
- -
- -

# sunlite

# **SPECIFICATIONS:**

### **General Characteristics**

| Bulb Shape              | Linear Tube        | Size           | 3'           |
|-------------------------|--------------------|----------------|--------------|
| Average Rated Hours     | 50000              | MOL (in)       | 35.24        |
| Finish                  | Frosted            | Diameter (in)  | 1            |
| Base                    | Medium 2-Pin (G13) |                |              |
| Average Life Span Years | 46                 | Product Data   |              |
| Dimmable                | Yes                | Case Unit Rate | 25           |
| Dimming Type            | 0-10V Low Voltage  | Pack Size      | 1            |
| Material                | Glass              | Item UPC       | 653703880372 |
|                         |                    | Warranty Voare | 5            |

#### **Electrical Characteristics**

| Amps                      | 0.114        |
|---------------------------|--------------|
| Watts                     | 12           |
| Volts                     | 120-277      |
| Equivalent Wattage        | F25T8, F36T8 |
| LED Chip Manufacturer     | SMD2835      |
| Power Factor              | >0.9         |
| Temperature               | -4°F - 113°F |
| Total Harmonic Distortion | <20%         |

#### **Light Characteristics**

| Lumens Brightness         | 1500                |
|---------------------------|---------------------|
| Color Rendering Index CRI | 83                  |
| Coating                   | PET Coating         |
| Emitted Color             | CCT Selectable      |
| Color Temperature Kelvin  | 30K/35K/40K/50K/65K |
| Beam Angle                | 320°                |

#### **Additional Features**

| Safety Rating Mark         |
|----------------------------|
| UL Rated Enclosed Fixtures |
| Safety Rated For Canada    |
| Safety Rated For USA       |
| DLC Classification         |
| Mercury Free               |

UL Listed - Damp Location Yes Yes Yes Standard Yes



#### **Product Dimensions**

| Case Unit Rate | 25           |
|----------------|--------------|
| Pack Size      | 1            |
| Item UPC       | 653703880372 |
| Warranty Years | 5            |