

A Series

Sunlite 05332-SU Compact Fluorescent A19 Light Bulb, 9 Watts (40W Equivalent), Medium Base (E26), 380 Lumens, 8,000 Hour Life Span, UL Listed, 65K - Daylight A Type

DESCRIPTION:

Sunlite CFL A19 Bulbs are an energy efficient, long life solution to your lighting needs. Using only 9 watts these compact fluorescent bulbs put out as much light as 40 watt incandescent bulbs. Daylight color temperature (6500K) provides ample illumination for anywhere you need bright light. 380 lumen output. Standard medium base (E26) works with a variety of lamps and fixtures. With a 8,000 hour life span these bulbs last more than 6 times longer than traditional bulbs. UL Listed.

FEATURES:

- COMPACT FLUORESCENT Sunlite CFL A19 Bulbs are an energy efficient, long life solution to your lighting needs.
- ENERGY EFFICIENT Using only 9 watts these compact fluorescent bulbs put out as much light as 40 watt incandescent bulbs. With a 8,000 hour life span these bulbs last up more than 6 times longer than traditional bulbs.
- DAYLIGHT -Daylight color temperature (6500K) provides ample illumination for anywhere you need bright light. 380 Lumen output.
- MEDIUM BASE Standard medium base (E26) works with a variety of lamps and fixtures.
- UL LISTED Tested to meet UL's strict safety and design standards.



sunlite

Product Dimensions

| Bulb Shape | A19 | MOL (in) | 4.245 | | | |
|----------------------------|--------------------|------------------------|----------------------------|--|--|--|
| Average Rated Hours | 8000 | Diameter (in) | 2.365" | | | |
| Base | Medium Screw (E26) | Item Dimension (in) | (W) 2.37 (H) 4.25 (D) 2.37 | | | |
| Average Life Span Years | 7 | Package Dimension (in) | (W) 2.5 (H) 4.69 (D) 2.5 | | | |
| | | Package Weight (lb) | 0.230 | | | |
| Electrical Characteristics | | | | | | |
| Watts | 9 | Product Data | | | | |
| Volts | 120 | Case Unit Rate | 12 | | | |
| | | Pack Size | 1 | | | |
| Light Characteristics | | Item UPC | 653703053325 | | | |
| Lumens Brightness | 380 | Package Type | Box | | | |
| Color Rendering Index CRI | 80 | U 11 | | | | |
| Emitted Color | Daylight | | | | | |
| Color Temperature Kelvin | 6500K | | | | | |
| Additional Features | | | | | | |

| Safety Rating Mark | UL Listed | | |
|---------------------------|-----------|--|--|
| FCT Label Mercury Content | Yes | | |





VARIATIONS:



| Item Number | Description | Watts | Eq Watts | Lumens | CRI | Kelvin Color | Hours | Pack |
|-------------|-------------|-------|----------|--------|-----|--------------|-------|------|
| 05332-SU | SLB9/65K | 9 | | 380 | 80 | 6500K DL | 8000 | 1 |
| 05309-SU | SLB14/65K | 14 | 40 | 750 | 80 | 6500K DL | 10000 | 1 |