

Spiral

Sunlite 05468-SU Dimmable Spiral CFL Light Bulb, 18 Watts (75W Equivalent), Medium Base (E26), 1200 Lumens, 10,000 Hour Life Span, UL Listed, 27K - Warm White 1 Pack

Dimmable Spiral

DESCRIPTION:

Sunlite Dimmable CFL Spiral Bulbs are an energy efficient, long life solution to your lighting needs. Using only 18 watts these compact fluorescent bulbs put out as much light as 75 watt incandescent bulbs. Warm white color temperature (2700K) provides comfortable lighting for bedrooms, living spaces, or anywhere you need warm light. Unlike most CFL bulbs this bulb can be dimmed when used with a lamp or fixture with dimming control. Bright 1200 Lumen output. Standard medium base (E26) works with a variety of lamps and fixtures. With a 10,000 hour life span these bulbs last up to 8 times longer than traditional bulbs. UL Listed.

FEATURES:

- **COMPACT FLUORESCENT** - Sunlite CFL Mini Spiral Bulbs are an energy efficient, long life solution to your lighting needs. They remain cooler to the touch than incandescent bulbs when lit. Standard medium base (E26) works with a variety of lamps and fixtures.
- **DIMMABLE** - Unlike most CFL bulbs this bulb can be dimmed when used with a lamp or fixture with dimming control.
- **ENERGY EFFICIENT** - Using only 18 watts these compact fluorescent bulbs put out as much light as 75 watt incandescent bulbs. With a 10,000 hour life span these bulbs last up to 8 times longer than traditional bulbs.
- **WARM WHITE** - Warm white color temperature (2700K) provides comfortable lighting for bathrooms, kitchens, bedrooms, living spaces, offices, or anywhere you need warm light. 1200 Lumen output.
- **UL LISTED** - Tested to meet UL's strict safety and design standards.



SPECIFICATIONS:

General Characteristics

Bulb Shape	T3
Average Rated Hours	10000
Base	Medium Screw (E26)
Average Life Span Years	9

Electrical Characteristics

Watts	18
Volts	120
Equivalent Wattage	75
Power Factor	0.5
Temperature	0° to 140°
Total Harmonic Distortion	150

Light Characteristics

Lumens Brightness	1200
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	2700K
Mercury Content	1.6MG

Additional Features

Safety Rating Mark	UL Listed
FCT Label Mercury Content	Yes

Product Dimensions

MOL (in)	5.28
Diameter (in)	2.115"
Item Dimension (in)	(W) 2.12 (H) 5.28 (D) 2.12
Package Dimension (in)	(W) 2.38 (H) 5.81 (D) 2.38
Package Weight (lb)	0.240

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703054681
Package Type	Box



VARIATIONS:



05468-SU



05467-SU



05479-SU

<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Eq Watts</i>	<i>Lumens</i>	<i>CRI</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
05468-SU	SL18/27K/D	18	75	1200	80	2700K WW	10000	1
05467-SU	SL20/27K/D	20		1350	80	2700K WW	10000	1
05479-SU	SL23/27K/D	23	100	1600	80	2700K WW	10000	1