

Spiral

Sunlite 05646-SU CFL Black Light Bulb (BLB), Halloween Lighting, Spiral Blacklight, 20 Watts, 120 Volts, Medium Base (E26), 463nm, UL Listed, 6 Pack

Black Light Spiral

DESCRIPTION:

The Sunlite 20-watt CFL black light bulb (BLB) emits ultraviolet (UV-A) light at 463nm wavelength perfect for lighting up reactive surfaces while not illuminating the surrounding areas. Ideal for creating a glow effect with colors like true white and neon hues for parties, clubs, and Halloween decorations. Can also be used for verifying security features on ID cards and currency and detecting pet stains on carpets or furniture that are not otherwise visible to the naked eye. Standard medium base (E26) works with a wide variety of lamps and fixtures. UL listed for safety and quality and features a long 8, 000 hour life span.

FEATURES:

- CFL BLACK LIGHT (BLB) The Sun lite 20 watt backlight bulb (BLB) emits ultraviolet (UV-A) light at 463nm wavelength perfect for lighting up reactive surfaces while not illuminating the surrounding areas.
- FESTIVE LIGHTING Ideal for creating a glow effect with colors like true white and neon hues for parties, clubs, and Halloween decorations.
- VERIFY AND DETECT Also great for verifying security features on ID cards and currency. Use to detect pet stains on carpets or furniture that are not otherwise visible to the naked eye.
- LONG LIFE SPAN Long 8, 000 hour life span means up to 7. 3 years of reliable service (based on 3 hours/day use).
- UL LISTED Tested to meet UL's strict testing standards for safety and reliability.





sunlite

Product Dimensions

Bulb Shape	<i>T</i> 3	MOL (in)	5.61
Nanometer	463	Diameter (in)	2.29"
Average Rated Hours	8000	Item Dimension (in)	(W) 2.29 (H) 5.61 (D) 2.29
Base	Medium Screw (E26)	Package Dimension (in)	(W) 5.35 (H) 6.29 (D) 8.11
Average Life Span Years	7	Package Weight (lb)	1.600
Electrical Characteristics		Product Data	
Watts	20	Case Unit Rate	4
Volts	120	Pack Size	6
Power Factor	0.5	Item UPC	653703056463
Light Characteristics		Package Type	Box
Lumens Brightness	15		
Color Rendering Index CRI	80		
Emitted Color	Black Light Blue		
Additional Features			

Additional Features

Safety Rating Mark

UL Listed

