

U-Shaped

Sunlite 32 Watt T8 U-Bend Tube, Mini Bi-Pin Base, Daylight

T8 U-Bend Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescent lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30235-SU FB32/SP865/6 6500K Color Temperature T8 U-Bend Tube Fluorescent 32 Watt lamp features a Medium Bi Pin base, provides a light output of 3000 lumens at a Color Rendering Index (CRI) of 83 and can last an average of 20000 hours.

FEATURES:

- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube
- T8 U-Bend Tube



SPECIFICATIONS:

General Characteristics

Bulb Shape	T8
Average Rated Hours	20000
Base	Miniature Bi-Pin (G5)
Average Life Span Years	18

Electrical Characteristics

Watts	32
--------------	----

Light Characteristics

Lumens Brightness	3000
Initial Lumens	3100
Mean Lumens	2925
Color Rendering Index CRI	83
Emitted Color	Daylight
Color Temperature Kelvin	6500K

Additional Features

Rohs Compliant	Yes
-----------------------	-----

Product Dimensions

MOL (in)	22.50
Diameter (in)	1"
Item Dimension (in)	(W) 0.99 (H) 23.4 (D) 6.94
Item Weight (lb)	0.510
Package Dimension (in)	(W) 1.2 (H) 7.2 (D) 22.9
Package Weight (lb)	0.750

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703302355

