

SUNLITE INSTALLATION INSTRUCTIONS

LED OUTDOOR FIXTURE

100-277VAC/60Hz Input, No Dimmable

READ AND FOLLOW SAFETY INFORMATION

CAUTION - Turn off the main power at the circuit breaker before installing and servicing the fixture to prevent possible injury from electric shock. All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections, obtain the services of a qualified electrician.

INSTALLATION & ASSEMBLY

1. Pull the power supply wires out from the outlet box (1). Attach the mounting backplate(2) to the outlet box using two mounting screws (3).
2. Make wire connections, connect the black supply wire (5) to black fixture wire (11), white supply wire (4) to white fixture wire(10) and the fixture ground wire(12) to supply ground wire(6) using wire nuts (7). Wrap all wire connections with electrical tape for secure connection.
3. Place the glass shade(14) of the lamp over the mounting bracket(11). Insert the fixture shade screws (12)
4. Place the fixture(11) of the lamp over the mounting bracket (2). Insert the fixture screws (13) and tighten to secure the lamp to the ceiling.
5. Install light bulbs (NOT included), DO NOT exceed wattage maximum as indicated on the rating label.
6. After installing the fixture, caulk upper 2/3 of wire connection enclosure to mounting surface. Leave bottom 1/3 un-caulked for drainage of any water that might leak into the enclosure. The manufacturer recommends a non-drying exterior caulking material. A good example is a clear silicone rubber sealant for exterior use.

