

Specialty

Sunlite 81249 LED Garage Light, 50 Watts (300W Equivalent), 6000 Lumens, 5000K Daylight, E26 Medium Base, UL Listed, 120-277V, Black, For Garage, Attic, Basement & Workshops

Garage

DESCRIPTION:

Upgrade your incandescent bulbs to a long-lasting Sunlite's LED Garage Light. This bulb is made to last thanks to its aluminum and polycarbonate material. It has three adjustable panels that go from 0 to 90 degrees to provide a wide range of illumination. This non-dimmable fixture has (E26) base socket that can easily be installed on most light sockets. Long 25,000-hour lifespan. These have a high lumen of 6000 and will last for years with no maintenance while using only 50 watts of power to provide 5000K Daylight comparable to that of a 300-watt bulb. Estimated annual energy costs of \$6.02 (Based on 3 Hrs/Day at \$0.11/kWh). Quick and easy installation onto standard bases. A straightforward installation allows you to get creative in any indoor setting. Easy to install using the mounting hardware that is included with installation instructions. UL Listed for safety and quality. Ideal for Garage, Attic, Basement, Workshops and more on a 120–277-volt service. Dimension: 3.9" H x 10" L.

FEATURES:

- DURABLE DESIGN This bulb is made to last thanks to its aluminum and polycarbonate material. It has three adjustable panels that go from 0 to 90 degrees to provide a wide range of illumination.
- MEDIUM BASE This non-dimmable fixture has (E26) base socket that can easily be installed on most light sockets. Long 25,000-hour lifespan.
- ENERGY EFFICIENT These have a high lumen of 6000 and will last for years with no maintenance while using only 50 watts of power to provide 5000K Daylight comparable to that of a 300-watt bulb. Estimated annual energy costs of \$6.02 (Based on 3 Hrs/Day at \$0.11/kWh).
- EASY INSTALLATION Quick and easy installation onto standard bases. A straightforward installation allows you to get creative in any indoor setting. Easy to install using the mounting hardware that is included with installation instructions.
- UL LISTED UL Listed for safety and quality. Ideal for Garage, Attic, Basement, Workshops and more Works on 120–277-volt service. Dimension: 3.9" H x 10" L.

sunlite

SPECIFICATIONS:

General Characteristics

Average Rated Hours

Bulb Shape

Dimmable

Material

Dimming Type

Finish

Base

Fan 25000 Black Medium Screw (E26) 23 No Not Dimmable Aluminum + PC

Electrical Characteristics

Average Life Span Years

Amps	0.450
Watts	50
Volts	120-277
Equivalent Wattage	300
LED Chip Manufacturer	2835
Power Factor	0.9
Temperature	-31°F - 104°F

Light Characteristics

Lumens Brightness	6000
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For USA	Yes
Mercury Free	Yes

Product Dimensions

MOL (in)	2.31
Diameter (in)	10.15
Item Dimension (in)	(W) 10.15 (H) 2.31 (D) 10.15
Package Dimension (in)	(W) 6.62 (H) 4.81 (D) 5.75
Package Weight (lb)	1.26

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703812496
Warranty Years	2
Package Type	Box