

G Series

Sunlite 81255 LED G40 Virtual Filament Globe Light Bulb, 3.5 Watts (15W Equivalent), 120 Lumens, Medium E26 Base, Clear Glass, Dimmable, Acrylic Inner Pillar, UL Listed, 2000K Amber, 1 Pack

Filament

DESCRIPTION:

Sunlite LED amber globe bulbs are designed to give you up to 15,000 hours of reliable service. That means fewer replacements for difficult to reach bulbs. These unique bulbs feature removable glass globe and virtual filament design. Output is a amber glow at 2000K. They are dimmable and energy efficient using only 3.5 watts of electricity. The annual operating cost is only \$0.42 (Based on 3 hours/day at \$0.11/kWh). And LED technology means they are cool to the touch when lit and instant-on at full brightness. The standard medium base (E26) make them the perfect bulb for wall sconces, decorative lamps, pendants, and many other fixtures. UL Listed for damp location installation. Ideal for both residential and commercial use.

FEATURES:

- UPGRADE TO LED Easily upgrade your decorative lighting with energy efficient 3.5 Watts (15W Equivalent), LED technology. These medium based (E26) bulbs are the perfect decorative bulb
- VIRTUAL FILAMENT STYLE These amber glass G40 globes feature a removable cover and virtual filament for a unique look. The etched zigzag pattern glows when lit creating an interesting effect. They are the perfect bulb for wall sconces, decorative lamps, pendants, and many other fixtures
- LONG LIFE BULBS With LED technology you save cost and the hassle of replacing hard to reach bulbs. They have an average life of 15,000 hours. The annual energy cost is a low \$0.42 per bulb (based on 3 hours/day at \$0. 11 per/kWh)
- DIMMABLE Emits a dimmable amber glow at 2000K. Cozy 120 lumen output ideal for decorative applications
- UL LISTED They are UL Listed for damp location installation. And LED technology means they are cool to the touch when lit and instant-on at full brightness. For residential and commercial applications





sunlite

SPECIFICATIONS:

General Characteristics

Product Dimensions

Bulb Shape	G40	MOL (in)	6.3
Average Rated Hours	15000	Diameter (in)	4.75
Finish	Amber	Item Dimension (in)	(W) 4.81 (H) 6.42 (D) 4.81
Base	Medium Screw (E26)	Item Weight (lb)	0.300
Average Life Span Years	14	Package Dimension (in)	(W) 5 (H) 7.3 (D) 5
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)	Package Weight (lb)	0.5
Dimmable	Yes	Product Data	
Material	Glass	Case Unit Rate	6
Electrical Characteristics		Pack Size Item UPC	1 653703812557
Watts	3.5	Warranty Years	2
Volts	120	Package Type	Box
Power Factor	0.7	r donago rypo	
Temperature	-20?-40?		
Light Characteristics			
Lumens Brightness	120		
Color Rendering Index CRI	80		



Emitted Color

Beam Angle

Additional Features Safety Rating Mark

Color Temperature Kelvin

744 Clinton Street Brooklyn, NY, 11231 | 718.768.7000

Warm White

UL Listed - Damp Location

2000K

300°