

A Series

Sunlite A19/5W/BL/WW LED A19 5W (40W Replacement) Blinker Light Bulbs, Medium (E26) Base, 3000K Warm White Blinker

DESCRIPTION:

Sunlite LED lamps are extremely energy efficient and will greatly reduce your energy costs. These lamps can last up to 25,000 hours making them virtually maintenance free. They contain no mercury elements and do not release any hazardous gasses so there no need to worry in case a bulb breaks and no need for any special recycling as with CFLs. With their high efficiency, their low wattage does not mean you lose out on brightness. This 120 volt, 5 watt, a type blinker features a medium base, produces a stunning warm white light at 500 lumens, and can fit right into your living room or into the most cutting edge, state of the art, lighting design project.

FEATURES:

- These lamps can last up to 25,000 hours making them virtually maintenance free
- This 120 volt, 5 watt, A-Type blinker bulb features a Medium (e26) base
- Produces a spectacular warm white light at a 500 lumens, while only using only 5 watts of energy
- Blinks at a rate of one blink per second. Contains no hazardous chemicals whatsoever, unlike some competing light bulbs
- Give your signs the power to effectively grab the attention of your customers and the general public with this powerfull blinking modern LED light bulb



SPECIFICATIONS:

General Characteristics

Bulb Shape	A19
Average Rated Hours	25000
Finish	White
Base	Medium Screw (E26)
Average Life Span Years	23
Dimmable	No
Material	Glass

Electrical Characteristics

Watts	5
Volts	120
Equivalent Wattage	40
LED Chip Manufacturer	Epistar
Power Factor	>0.5

Light Characteristics

Lumens Brightness	500
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	150°

Product Dimensions

MOL (in)	4.33
Diameter (in)	2.36
Item Dimension (in)	(W) 2.25 (H) 4 (D) 2.25
Package Dimension (in)	(W) 2.5 (H) 2.6 (D) 4.4
Package Weight (lb)	0.250

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703802046
Package Type	Box